
DELTALIGHT




INFORM SQ P392-6 DOWN 93067

REFERENCE 25570 9320 W-B

AVAILABLE IN
BLACK-BLACK 25570 9320 B-B
BLACK-FLEMISH GOLD 25570 9320 B-FG
WHITE-BLACK 25570 9320 W-B
WHITE-WHITE 25570 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	72 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 600/900mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 3000K / 1602-2315lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	4630lm // 33,4W // 138lm/W
LED TECHNICS (LUMINAIRE)	4042lm // 38,4W // 105lm/W

Requirements

INFORM POWER SUPPLY 45W
INFORM SQ POWERBOX L 50W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


INFORM SQ P392-6 DOWN 93067

25570 9320 W-B

For detailed installation instructions, please consult the manual : **25570_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION


Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0385 INFORM POWER SUPPLY 45W DIM5 1 ☐

Dimtype: DALI



25510 0430 INFORM POWER SUPPLY 45W 1 ☐

Dimtype: non-dimmable

DELTALIGHT

INFORM SQ P392-6 DOWN 93067


25570 9320 W-B

Power box

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0480 B INFORM SQ POWERBOX L 50W B — 1

Dimtype: non-dimmable

25510 0480 W INFORM SQ POWERBOX L 50W W — 1




25510 0495 B INFORM SQ POWERBOX L 50W DIM5 B — 1

Dimtype: DALI

25510 0495 W INFORM SQ POWERBOX L 50W DIM5 W — 1


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B


204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B




204 00 90 W COVERSET R 90 W





204 00 100 ANO COVERSET R 100 ANO

INFORM SQ P392-6 DOWN 93067

25570 9320 W-B

	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐
	**204 62 62 ANO** COVERSET S 62 ANO	☐
	204 62 62 B COVERSET S 62 B	☐
	204 62 62 W COVERSET S 62 W	☐
	**204 80 80 ANO** COVERSET S 80 ANO	☐
	204 80 80 B COVERSET S 80 B	☐
	204 80 80 W COVERSET S 80 W	☐
	**204 90 90 ANO** COVERSET S 90 ANO	☐
	204 90 90 B COVERSET S 90 B	☐
	204 90 90 W COVERSET S 90 W	☐

Suspension parts

	**328 10 01** SUSPENSION TRIMLESS O.F.A. **Cutout dimension (mm): 62 (CONCRETE: 102)**	☐
	**15225 0340 B** SUSPENSION ST B **Cutout dimension (mm): 27**	☐


DELTALIGHT

INFORM SQ P392-6 DOWN 93067

25570 9320 W-B

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: