



INFORM SQ P392-6 DOWN 93067

25570 9320 W-B


AVAILABLE IN

BLACK-BLACK 25570 9320 B-B

BLACK-FLEMISH GOLD 25570 9320 B-FG

WHITE-BLACK 25570 9320 W-B

WHITE-WHITE 25570 9320 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	72 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 600/900mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 3000K / 1602-2315lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	4630lm // 33,4W // 138lm/W
LED TECHNICS (LUMINAIRE)	4042lm // 38,4W // 105lm/W

Requirements

INFORM POWER SUPPLY 45W
INFORM SQ POWERBOX L 50W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTA LIGHT


INFORM SQ P392-6 DOWN 93067

25570 9320 W-B

For detailed installation instructions, please consult the manual : [25570_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐



LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.






Min current | Max current

	25510 0385 INFORM POWER SUPPLY 45W DIMS	1 ☐
	Dimtype: DALI	
	25510 0430 INFORM POWER SUPPLY 45W	1 ☐
	Dimtype: non-dimmable	

DELTALIGHT

INFORM SQ P392-6 DOWN 93067




25570 9320 W-B

Power box		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '!' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	25510 0480 B INFORM SQ POWERBOX L 50W B	1
	Dimtype: non-dimmable	
	25510 0480 W INFORM SQ POWERBOX L 50W W	1
	25510 0495 B INFORM SQ POWERBOX L 50W DIM5 B	1
	Dimtype: DALI	
	25510 0495 W INFORM SQ POWERBOX L 50W DIM5 W	1
Coversets		
	204 00 62 ANO COVERSET R 62 ANO	
	204 00 62 B COVERSET R 62 B	
	204 00 62 W COVERSET R 62 W	
	204 00 90 ANO COVERSET R 90 ANO	
	204 00 90 B COVERSET R 90 B	
	204 00 90 W COVERSET R 90 W	
	204 00 100 ANO COVERSET R 100 ANO	



DELTALIGHT

INFORM SQ P392-6 DOWN 93067

25570 9320 W-B

	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
		Cutout dimension (mm): 27	

DELTALIGHT

INFORM SQ P392-6 DOWN 93067


25570 9320 W-B

15225 0340 W

SUSPENSION ST W

☐

Electric connection parts



328 10 03

CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B

CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W

CONNECTION ST W

☐

Notes: