



COMPO L IP44 93041

9 15755 9330 B



AVAILABLE IN

NOIR 9 15755 9330 B

CHROME 9 15755 9330 C

CHROME FONCÉ 9 15755 9330 DC

BLANC 9 15755 9330 W



[View on website](#)



General info

LOCATION	interieur-exterieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.476
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 52) / 3000K / 2101lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	2101lm // 17,2W // 123lm/W
LED TECHNICS (LUMINAIRE)	1618lm // 19,8W // 82lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B

COMPO L LINEAR SPREAD LENS

COMPO L SPREAD LENS

COMPO L SOFTENING LENS

COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : [9_15755_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	15710 0030 - MOUNTING KIT COMPO L TRIM Required
	15710 0060 - MOUNTING KIT COMPO L TRIMLESS Required
	15710 0030 - MOUNTING KIT COMPO L TRIM Required
	15710 0060 - MOUNTING KIT COMPO L TRIMLESS Required
	15710 0030 - MOUNTING KIT COMPO L TRIM Required
	15710 0060 - MOUNTING KIT COMPO L TRIMLESS Required

FINISH YOUR SPECIFICATION


alimentation led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 3200 LED POWER SUPPLY MULTIPOWER 15W NO DIM 300mA	1->2 ☐
15710 3600 LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA	1 ☐
15710 3700 LED POWER SUPPLY MULTIPOWER 10W DIM8 300mA	1 ☐
15710 4200 LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA	1 ☐
15710 4400 LED POWER SUPPLY MULTIPOWER 12W DIM1 300mA	1->2 ☐
15710 4700 LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA	1 ☐
15710 5200 LED POWER SUPPLY MULTIPOWER 12W DALI DT6 300mA	1->2 ☐
Dimtype: DALI	
15710 5400 LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1 ☐
Dimtype: DALI	

DELTALIGHT

COMPO L IP44 93041

9 15755 9330 B

kit de montage



15710 0030 B MOUNTING KIT COMPO L TRIM B

☐

Cutout dimension (mm): 92



15710 0060 MOUNTING KIT COMPO L TRIMLESS

☐

Cutout dimension (mm): 92

modifier les dispositifs de lumière

15710 2100 B COMPO L HONEYCOMB SINGLE USE B

☐

15710 2110 COMPO L LINEAR SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2120 COMPO L SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2130 COMPO L SOFTENING LENS

☐

Cutout dimension (mm): 42

15710 2140 COMPO L GLASS SBL

☐

Cutout dimension (mm): 42

Notes: