
DELTALIGHT




# DEEP RINGO HE 94040

**REFERENCE** 19440 9430 BRBB

AVAILABLE IN
**BLACK** 19440 9430 B
**BRUSHED ALU** 19440 9430 BRA
**BRUSHED ANTHRACITE** 19440 9430 BRAT
**BRUSHED BROWN BRONZE** 19440 9430 BRBB
**BRUSHED COPPER** 19440 9430 BRCU
**BRUSHED GOLD** 19440 9430 BRG
**BRUSHED OLD BRONZE** 19440 9430 BROB
**CREAM** 19440 9430 CR
**FLEMISH BRONZE** 19440 9430 FBR
**FLEMISH GOLD** 19440 9430 FG
**GOLD COLOURED** 19440 9430 GC
**PIANO BLACK** 19440 9430 PB
**WHITE** 19440 9430 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - 76 |
| **RECESSED DEPTH (MM)** | 90 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | min.5 |
| **INGRESS PROTECTION** | IP43/20 |
| **WEIGHT (KG)** | 0.2 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | LENS WFL-40°<br>EXCL.LED POWER SUPPLY 350mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | D |
| **CERTIFICATES** | EPD, LCA |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 6W / CRI>90 (R9: 60) / 4000K / 975lm |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 40° |
| **LED TECHNICS (LIGHT SOURCE)** | 975lm // 6W // 163lm/W |
| **LED TECHNICS (LUMINAIRE)** | 793lm // 6,9W // 115lm/W |

**Remarks**

High Efficacy : > 100lm/W

**Requirements**

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT

# DEEP RINGO HE 94040

19440 9430 BRBB


For detailed installation instructions, please consult the manual : **19440_XXX0_HAND.pdf**

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|---|
|  **System ceiling** | - |
|  **Plasterboard** | - |
|  **Stucanet** | - |
|  **Wood** | - |
|  **Concrete** | - |
|  **Concrete + plaster** | - |
|  **Lintel + plaster** | - |
|  **Hollow-core slab** | - |
|  **Hollow-core slab + plaster** | - |
|  **Stretched ceiling** | - |

## FINISH YOUR SPECIFICATION

### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐

**Cutout dimension (mm): 27**

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐

DELTALIGHT

# DEEP RINGO HE 94040


19440 9430 BRBB

## LED power supplies

## # of Fixtures

**Min current | Max current**


# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 91** LED POWER SUPPLY 350mA-DC / 15W — 2(1)

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**




**300 90 110** LED POWER SUPPLY 350mA-DC / 10W DIM8 — 1

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 42**




**300 90 116** LED POWER SUPPLY 350mA-DC / 18W DIM8 — 2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**




**21012 0515** LED POWER SUPPLY MULTI POWER DIM5 — 1(1)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**21012 0520** LED POWER SUPPLY 350mA-DC / 8W — 1(0)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 47**




**21012 0575** LED POWER SUPPLY MULTI POWER DIM5 — 2->3(2)

**Dimtype: DALI**

**Cutout dimension (mm): 55**

Notes: