



NOCTA SQ155 2VWFL 927

30124 9200 B

AVAILABLE IN


ALU GREY 30124 9200 A

BLACK 30124 9200 B

FLEMISH BRONZE OUTDOOR 30124 9200 FBRX

ANTHRACITE 30124 9200 N

WHITE 30124 9200 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x TUBE INCL.LED POWER SUPPLY 700 mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm)
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	440lm // 4W // 110lm/W
LED TECHNICS (LUMINAIRE)	131lm // 4,6W // 28lm/W

For detailed installation instructions, please consult the manual : [30124_XXX0_HAND.pdf](#)

DELTALIGHT

NOCTA SQ155 2VWFL 927

30124 9200 B

Notes: