



ENTERO RD-M TRIMLESS SOFT 93018



28431 9010 GC

AVAILABLE IN

NOIR 28431 9010 B

ENTIÈREMENT BLANC 28431 9010 FW

COULEUR OR 28431 9010 GC



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif
INFORMATION	REFLECTOR SP-18° EXCL.DIMMABLE LED POWER SUPPLY 450mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,1W / CRI>90 (R9: 50) / 3000K-1800K / 1618lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	1618lm // 16,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	1190lm // 18,5W // 64lm/W

Requirements

MOUNTING KIT ENTERO ROUND M

LED POWER SUPPLY 450mA-DC DIM (Remote)

Accessories

ENTERO M HONEYCOMB

ENTERO M LINEAR SPREAD LENS

ENTERO M SPREAD LENS

ENTERO M SOFTENING LENS

ENTERO M GLASS SBL

ENTERO RD-M TRIMLESS SOFT 93018

28431 9010 GC


For detailed installation instructions, please consult the manual : [28431_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required
	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required

FINISH YOUR SPECIFICATION

les batteries de secours

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

les alimentations led








of Fixtures

 web2print_power_supply_info_box

Min current | Max current

ENTERO RD-M TRIMLESS SOFT 93018

28431 9010 GC

	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	1(0)	☐
	Dimtype: 1 à 10 V ou bouton poussoir		
	Cutout dimension (mm): 72		
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1(0)	☐
	Dimtype: DALI		
	Cutout dimension (mm): 72		
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(0)	☐
	Dimtype: 1 à 10 V ou bouton poussoir		
	Cutout dimension (mm): 55		
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(0)	☐
	Dimtype: DALI		
	Cutout dimension (mm): 55		
	300 90 135 LED POWER SUPPLY MULTI-POWER HV	2->2	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 90		
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 54		
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 48		

kit de montage


	28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.		☐
	Cutout dimension (mm): 127		

DELTALIGHT

ENTERO RD-M TRIMLESS SOFT 93018

28431 9010 GC

kit de montage plafond tendu



28400 0080 MOUNTING KIT ENTERO RD-M CSC

☐


28400 0140 MOUNTING KIT ENTERO RD-M WSC

☐


modifier les dispositifs de lumière




28500 0070 ENTERO M LINEAR SPREAD LENS

☐


28500 0080 ENTERO M SPREAD LENS

☐


28500 0090 ENTERO M SOFTENING LENS

☐

28500 0100 ENTERO M GLASS SBL

☐

28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

☐

28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B

☐

DELTALIGHT

ENTERO RD-M TRIMLESS SOFT 93018

28431 9010 GC

Réflecteur / lentille remplaçable



24611 0220 SPY 66 REFLECTOR 18°

☐

24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

Notes: