
DELTALIGHT




SUPERNOVA LINE 125 TW DOWN-UP DIM5

REFERENCE 274 96 12 26 ED5 B

AVAILABLE IN
BLACK 274 96 12 26 ED5 B
WHITE 274 96 12 26 ED5 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	21
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY - DALI (DT6) CABLING 2 CIRCUITS 4 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm²

Electrical info	
ELECTRICAL	120-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K : LED cluster 179W / CRI>80 / 2700K - 5700K / 16942lm UP @ 2700K : LED cluster 50W / CRI>80 / 2700K - 5700K / 4122lm Or DOWN @ 5700K : LED cluster 179W / CRI>80 / 2700K - 5700K / 19338lm UP @ 5700K : LED cluster 50W / CRI>80 / 2700K - 5700K / 4530lm
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 16942 lm // 179 W // 95 lm/W UP @ 2700K: 4122 lm // 50 W // 82 lm/W Or DOWN @ 5700K: 19338 lm // 179 W // 108 lm/W UP @ 5700K: 4530 lm // 50 W // 91 lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 13469lm // 206W // 65lm/W UP @ 2700K: 3603lm // 58W // 63lm/W Or DOWN @ 5700K: 15316lm // 206W // 74lm/W UP @ 5700K: 3959lm // 58W // 69lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



SUPERNOVA LINE 125 TW DOWN-UP DIM5

274 96 12 26 ED5 B



For detailed installation instructions, please consult the manual : **274_96_12_26_ED5_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply

	**203 99 55 ANO**	CABLE BASE R ANO	☐
	203 99 55 B	CABLE BASE R B	☐
	203 99 55 W	CABLE BASE R W	☐
	**203 99 56 ANO**	CABLE BASE S ANO	☐
	203 99 56 B	CABLE BASE S B	☐
	203 99 56 W	CABLE BASE S W	☐





Coversets

	**204 00 62 ANO**	COVERSET R 62 ANO	☐
	204 00 62 B	COVERSET R 62 B	☐
	204 00 62 W	COVERSET R 62 W	☐
	**204 00 90 ANO**	COVERSET R 90 ANO	☐

DELTALIGHT

SUPERNOVA LINE 125 TW DOWN-UP DIM5

274 96 12 26 ED5 B


	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA LINE 125 TW DOWN-UP DIM5


274 96 12 26 ED5 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: