



SPY 52 ON 1 93020 DIM8


19826 9328 W-W

BESCHIKBAAR IN

ZWART-ZWART 19826 9328 B-B

VOLLEDIG WIT 19826 9328 FW

WIT-WIT 19826 9328 W-W



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Opbouw
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.6
RICHTBAARHEID	0° tot 90° zwenkbaar, 355° roteerbaar
INFO	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply Optional REFLECTORS 30° & 45° available

Elektrische info

INGANGSSPANNING	220-240V / 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	net-dimbaar (fase afsnijding)
ENERGIE KLASSE	D
CERTIFICATEN	CB, ENEC, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@500mA: LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm Or @350mA: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30-15 WAARDEN	@500mA: rf: 90 / Rg: 99 @350mA: rf: 90 / Rg: 99
SDCM	SDCM1
RISK-GROEP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNIEK (LICHTBRON)	@500mA: 1089lm // 8,6W // 127lm/W Or @350mA: 787lm // 5,8W // 135lm/W
LED TECHNIEK (TOESTEL)	@500mA: 682lm // 9,9W // 69lm/W Or @350mA: 493lm // 6,7W // 74lm/W

Benodigdheden

SPY 52 TUBE

Accessoires

HONEYCOMB 42

SPREAD LENS 42

DELTALIGHT

SPY 52 ON 1 93020 DIM8





19826 9328 W-W

LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

Voor gedetailleerde montage gegevens, consulteer de handleiding : [19826_XXX8_HAND.pdf](#)

VERVOLLEDIG UW SPECIFICATIE

Licht veranderende onderdelen

	¹³ 19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	¹³ 19810 0020 LINEAR SPREAD LENS 42	☐
	¹³ 19810 0030 SPREAD LENS 42	☐
	¹³ 19810 0040 SOFTENING LENS 42	☐
	¹³ 19810 0050 GLASS SBL 42	☐
	¹⁴ 19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐

DELTALIGHT

SPY 52 ON 1 93020 DIM8

19826 9328 W-W

Maak je product af

	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

Vervangbare reflector / lens

	19810 0180 SPY 52 REFLECTOR 20°	☐
	19810 0190 SPY 52 REFLECTOR 45°	☐
	19810 0240 SPY 52 REFLECTOR 30°	☐

Notes: