

OML50 - LED ARRAY D HE  
CORNER X 940 DIM5

31059 9405

 [Bekijk op website](#)



| Algemene info            |                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------|
| LOCATIE                  | binnen                                                                                             |
| STOF EN WATERDICHTHEID   | IP20                                                                                               |
| GEWICHT (KG)             | 0                                                                                                  |
| INFO                     | CLUSTER DOWN: 2898lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |
| Elektrische info         |                                                                                                    |
| INGANGSSPANNING          | 220-240V / 0 50-60Hz                                                                               |
| KLASSE                   | I                                                                                                  |
| VOEDING                  | YES                                                                                                |
| DIM TYPE                 | DALI                                                                                               |
| ENERGIE KLASSE           | D                                                                                                  |
| CERTIFICATEN             | EPD, RCM                                                                                           |
| Info lichtbron           |                                                                                                    |
| LIGHTSOURCE NAME         | LED                                                                                                |
| LICHTBRON                | 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm)                                         |
| TM-30-15 WAARDEN         | Rf: 90 / Rg: 101                                                                                   |
| SDCM                     | SDCM3                                                                                              |
| RISK-GROEP               | RG1                                                                                                |
| LM80                     | L80 > 60000                                                                                        |
| LED TECHNIEK (LICHTBRON) | 3802lm // 22,2W // 171lm/W                                                                         |

| Opties                |
|-----------------------|
| WIRELESS CONTROL DIM5 |

Notes: