

OML50 - LED ARRAY D HE  
CORNER X 940 DIM5

31059 9405

 [View on website](#)



| General info                |                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                             |
| INGRESS PROTECTION          | IP20                                                                                               |
| WEIGHT (KG)                 | 0                                                                                                  |
| INFORMATION                 | CLUSTER DOWN: 2898lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |
| Electrical info             |                                                                                                    |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                               |
| CLASS                       | I                                                                                                  |
| POWER SUPPLY                | YES                                                                                                |
| DIM TYPE                    | DALI                                                                                               |
| ENERGY CLASS                | D                                                                                                  |
| CERTIFICATES                | EPD, RCM                                                                                           |
| Lightsource info            |                                                                                                    |
| LIGHTSOURCE NAME            | LED                                                                                                |
| LIGHTSOURCE                 | 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 4000K / 1901lm)                                         |
| TM-30 VALUES                | Rf: 90 / Rg: 101                                                                                   |
| SDCM                        | SDCM3                                                                                              |
| RISKGROUP                   | RG1                                                                                                |
| LM80                        | L80 > 60000                                                                                        |
| LED TECHNICS (LIGHT SOURCE) | 3802lm // 22,2W // 171lm/W                                                                         |

| Options               |
|-----------------------|
| WIRELESS CONTROL DIM5 |

Notes: