

INFORM SQ F200-7 93067

25526 9320 B-B


AVAILABLE IN

BLACK-BLACK 25526 9320 B-B

BLACK-FLEMISH GOLD 25526 9320 B-FG

WHITE-BLACK 25526 9320 W-B

WHITE-WHITE 25526 9320 W-W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	non adjustable
INFORMATION	84 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 700/1050mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 24,6-39,1W / CRI>90 (R9: 50) / 3000K / 3738-5401lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	5401lm // 39,1W // 138lm/W
LED TECHNICS (LUMINAIRE)	4715lm // 45W // 105lm/W

Requirements

INFORM POWER SUPPLY 45W

For detailed installation instructions, please consult the manual : [25526_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0070 INFORM POWER SUPPLY 50W

1


Dimtype: non-dimmable



25510 0385 INFORM POWER SUPPLY 45W DIM5

1

Dimtype: DALI



25510 0430 INFORM POWER SUPPLY 45W

1

Dimtype: non-dimmable

Notes: