





M20/M26H - SPY 39 FRAMER 930 DIM5

23418 9305 B

AVAILABLE IN
BLACK 23418 9305 B



 [View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.3 |
| ADJUSTABILITY | 0° to 85° swiveling, 355° rotatable |
| INFORMATION | EXCL.LED POWER SUPPLY 48V-DC |

Electrical info

| | |
|---------------------|--------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | DALI |
| ENERGY CLASS | E |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm |
| TM-30 VALUES | rf: 90 / Rg: 99 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 1018lm // 8,6W // 118lm/W |
| LED TECHNICS (LUMINAIRE) | 347lm // 9,9W // 35lm/W |

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23418_XXX5_HAND.pdf](#)

DELTALIGHT

M20/M26H - SPY 39 FRAMER 930 DIM5

23418 9305 B

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL


Available Colours



30411 9205 SHIFTLINE M26H + SBL 2m DIM5



30411 9305 SHIFTLINE M26H + SBL 2m DIM5




30412 9205 SHIFTLINE M26H + SBL 3m DIM5




DELTALIGHT

M20/M26H - SPY 39 FRAMER 930 DIM5


23418 9305 B



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5




SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m



DELTALIGHT

M20/M26H - SPY 39 FRAMER 930 DIM5

23418 9305 B




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: