



M26L - OCTAV 27 92730 DIM5

REFERENCE

29015 9225 B

AVAILABLE IN



BLACK 29015 9225 B

FLEMISH BRONZE 29015 9225 FBR

FLEMISH GOLD 29015 9225 FG

GOLD COLOURED 29015 9225 GC

WHITE 29015 9225 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 27 L TUBE B included

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	276lm // 6,7W // 41lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements





LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **29015_XXX5_HAND.pdf**




M26L - OCTAV 27 92730 DIM5

29015 9225 B

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
<div><div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		Min current Max current
<div><div></div><div>300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN</div></div>	Dimtype: non-dimmable	15 <input type="text"/>
<div><div></div><div>300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN</div></div>	Dimtype: non-dimmable	36 <input type="text"/>
<div><div></div><div>21012 0230 LED POWER SUPPLY 48V-DC / 100W</div></div>	Dimtype: non-dimmable Cutout dimension (mm): 40	15 <input type="text"/>
<div><div></div><div>21012 0240 LED POWER SUPPLY 48V-DC / 200W</div></div>	Dimtype: non-dimmable Cutout dimension (mm): 40	30 <input type="text"/>


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
<div><div></div><div>23358 0000 SLM26L - PROFILE</div></div>	<div><div></div><div></div></div>
<div><div></div><div>23358 0010 SLM26L - PROFILE 1m</div></div>	<div><div></div><div></div></div>
<div><div></div><div>23358 0020 SLM26L - PROFILE 2m</div></div>	<div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div>

DELTALIGHT

M26L - OCTAV 27 92730 DIM5

29015 9225 B



23358 0030 SLM26L - PROFILE 3m



Notes: