



ENTERO RD-S TRIMLESS 92745



28425 9230 B

AVAILABLE IN

NOIR 28425 9230 B

ENTIÈREMENT BLANC 28425 9230 FW

COULEUR OR 28425 9230 GC



 [View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	105
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.235
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif
INFORMATION	REFLECTOR WFL-45° EXCL. LED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 20° & 30° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-12,4W / CRI>90 (R9: 60) / 2700K / 753-1403lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	1076lm // 14,3W // 75lm/W

Remarks

Max.500mA when using accessories

Requirements

MOUNTING KIT ENTERO ROUND S

MOUNTING KIT AIR 105

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

Accessories

ENTERO S HONEYCOMB

ENTERO S LINEAR SPREAD LENS

ENTERO S SPREAD LENS

ENTERO S SOFTENING LENS

ENTERO RD-S TRIMLESS 92745

28425 9230 B

ENTERO S GLASS SBL


For detailed installation instructions, please consult the manual : [28425_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Plasterboard	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Stucanet	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Concrete + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Lintel + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Hollow-core slab + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Stretched ceiling	 28400 0070 - MOUNTING KIT ENTERO RD-S CSC	Required
	 28400 0130 - MOUNTING KIT ENTERO RD-S WSC	Required
 Ventilation in plasterboard	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0110 - MOUNTING KIT SIDE AIR 105	Required
	 29810 0120 - MOUNTING KIT NO AIR 105	Required
 Ventilation in concrete + plaster	 29810 0120 - MOUNTING KIT NO AIR 105	Required
	 29810 0130 - MOUNTING KIT TOP AIR 105	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required

FINISH YOUR SPECIFICATION

les batteries de secours











DELTALIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 B







21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐

les alimentations led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2 ☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2 ☐
	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2 ☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2 ☐
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2 ☐
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2 ☐
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2 ☐
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2 ☐











ENTERO RD-S TRIMLESS 92745

28425 9230 B

	300 48 700 ED1	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1	2	☐
Dimtype: 1 à 10 V				
Cutout dimension (mm): 30				
	300 48 700 ED5	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	2	☐
Dimtype: DALI				
Cutout dimension (mm): 45				
	300 48 700 MDL	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	2	☐
Dimtype: non dimmable				
Cutout dimension (mm): 30				
	300 48 700 WDL	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	2	☐
Dimtype: WDL = dimmable sans fil				
Cutout dimension (mm): 45				
	300 90 61	LED POWER SUPPLY MULTI-POWER DIM6	2 2 2	☐
Dimtype: fin de phase ou bouton poussoir				
Cutout dimension (mm): 56				
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	4(4) 4(4) 4(3)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
Cutout dimension (mm): 82				
	300 90 64	LED POWER SUPPLY MULTI-POWER DIM7	2(2) 2(1) 2(1)	☐
Dimtype: 1 à 10 V ou bouton poussoir				
Cutout dimension (mm): 72				
	300 90 67	LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2 - 2	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	2(2) 2(1) 2(1)	☐
Dimtype: DALI				
Cutout dimension (mm): 72				
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) 6(4) 4(3)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
Cutout dimension (mm): 84				

ENTERO RD-S TRIMLESS 92745

28425 9230 B

	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	3(2) 2(1) 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1) 1(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	3->4 2->4 2->4	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 2 2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	3 3 2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3 3 3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	4(4) 3(3) 3(3)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	3 3 2	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2 0 0	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 1	☐

ENTERO RD-S TRIMLESS 92745


28425 9230 B

	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->3 2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2 2 1	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

DELTALIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 B



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

Dimtype: DALI

Cutout dimension (mm): 30

2

☐

kit de montage



28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

Cutout dimension (mm): 105

☐




28500 0220 MOUNTING KIT DEEP ENTERO RD-S TRIMLESS

Cutout dimension (mm): 133

☐

kit de montage plafond tendu



28400 0070 MOUNTING KIT ENTERO RD-S CSC


☐



28400 0130 MOUNTING KIT ENTERO RD-S WSC

☐


kit de montage - side air + light



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168

☐



29810 0110 MOUNTING KIT SIDE AIR 105

Cutout dimension (mm): 168


☐

DELTALIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 B

kit de montage - top air + light




29810 0130 MOUNTING KIT TOP AIR 105

Cutout dimension (mm): 135

☐

kit de montage - top air only




29810 0200 MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135

☐

kit de montage - no air




29810 0120 MOUNTING KIT NO AIR 105


Cutout dimension (mm): 168

☐


modifier les dispositifs de lumière




28500 0010 ENTERO S LINEAR SPREAD LENS

☐

28500 0020 ENTERO S SPREAD LENS

☐

28500 0030 ENTERO S SOFTENING LENS

☐


28500 0040 ENTERO S GLASS SBL

☐


DELTALIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 B




28500 0050 B ENTERO S HONEYCOMB SINGLE USE B

☐

28500 0060 B ENTERO S HONEYCOMB DOUBLE USE B

☐

Réflecteur / lentille remplaçable



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: