
DELTALIGHT




SOLI - 52 SOFT 93045 DIM5

REFERENCE 27185 9035 W

AVAILABLE IN
BLACK 27185 9035 B
GOLD COLOURED 27185 9035 GC
WHITE 27185 9035 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 20° & 30° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	664lm // 11,7W // 57lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT


SOLI - 52 SOFT 93045 DIM5

27185 9035 W


For detailed installation instructions, please consult the manual : **27185 _XXX5_HAND.pdf** , **27185_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION


Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B ☐




19810 0020 LINEAR SPREAD LENS 42 ☐




19810 0030 SPREAD LENS 42 ☐



19810 0040 SOFTENING LENS 42 ☐




19810 0050 GLASS SBL 42 ☐



19810 0060 B HONEYCOMB 42 DOUBLE USE B ☐

Finish your product



19810 0100 B SPY 52 TUBE B ☐

SOLI - 52 SOFT 93045 DIM5


27185 9035 W

19810 0100 FBR	SPY 52 TUBE FBR
19810 0100 FG	SPY 52 TUBE FG
19810 0100 GC	SPY 52 TUBE GC
19810 0100 W	SPY 52 TUBE W


Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°





19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 **27111 0020** SOLI - PROFILE 2m	
 **27111 0030** SOLI - PROFILE 3m	

Notes:

SOLI - 52 SOFT 93045 DIM5

27185 9035 W