

## SPM20 - SPY 522 AIR 92720

29815 9220 B

AVAILABLE IN



**BLACK** 29815 9220 B

**FLEMISH BRONZE** 29815 9220 FBR

**FLEMISH GOLD** 29815 9220 FG

**GOLD COLOURED** 29815 9220 GC

**WHITE** 29815 9220 W



 [View on website](#)



### General info

|                               |   |
|-------------------------------|---|
| <b>LOCATION</b>               | indoor  |
| <b>INSTALLATION</b>           | Ceiling Recessed  |
| <b>CUTOUT SHAPE/SIZE (MM)</b> | rectangle - KIT   |
| <b>INGRESS PROTECTION</b>     | IP20  |
| <b>WEIGHT (KG)</b>            | 0.7   |
| <b>ADJUSTABILITY</b>          | 0° to 90° swiveling, 355° rotatable   |
| <b>INFORMATION</b>            | REFLECTOR FL-20°<br>EXCL.LED POWER SUPPLY 350-700mA-DC<br>Optional REFLECTORS 30° & 45° available |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | F                         |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | 2 x (LED array 5,8-12,4W / CRI>90 (R9: 60) / 2700K / 753-1403lm) |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100   |
| <b>SDCM</b>                        | SDCM1  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L90B10 > 50000   |
| <b>BEAMANGLE</b>                   | 20°  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 2806lm // 24,8W // 113lm/W                                       |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1758lm // 28,5W // 62lm/W  |

### Requirements

SPM20 - AIR KIT 1  
SPY 52 TUBE  
LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

### Accessories

HONEYCOMB 42  
SPREAD LENS 42  
LINEAR SPREAD LENS 42  
SOFTENING LENS 42  
GLASS SBL 42

# DELTALIGHT

## SPM20 - SPY 522 AIR 92720

29815 9220 B


For detailed installation instructions, please consult the manual : [29815\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

| Ceiling Type   | Mounting Kit   |          |
|--|--|----------|
|  Ventilation in plasterboard |  29810 1010 - SPM20 - AIR KIT 1 | Required |

### FINISH YOUR SPECIFICATION

#### AIR kit for M20



**29810 1010** SPM20 - AIR KIT 1

Cutout dimension (mm): 50 x 310


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

# DELTALIGHT

## SPM20 - SPY 522 AIR 92720

29815 9220 B



**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30



**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



**300 48 700 ED1** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30



**300 48 700 ED5** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 700 MDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 700 WDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

1|1|1

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

2(2) | 2(2) | 2(1)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82

# DELTALIGHT

## SPM20 - SPY 522 AIR 92720

29815 9220 B



**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

1(1) | 1(1/2) | 1(1/2)



Dimtype: 1-10V or push button

Cutout dimension (mm): 72



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

1 | - | 1



Dimtype: 1-10V or DALI or push button



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

1(1) | 1(1/2) | 1(1/2)



Dimtype: DALI

Cutout dimension (mm): 72



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

3(3) | 3(2) | 2(1)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

1(1) | 1(1/2) | 1/2(1/2)



Dimtype: 1-10V or push button

Cutout dimension (mm): 55



**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1) | 1(1/2) | 1/2(1/2)



Dimtype: DALI

Cutout dimension (mm): 55



**300 90 135** LED POWER SUPPLY MULTI-POWER HV

2 | 2 | 2



Dimtype: non-dimmable

Cutout dimension (mm): 90




**21012 0010** LED POWER SUPPLY MULTI POWER

1 | 1 | 1



Dimtype: non-dimmable

Cutout dimension (mm): 50




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

1 | 1 | 1



Dimtype: 1-10V

Cutout dimension (mm): 54



**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

1 | 1 | 1




Dimtype: DALI

Cutout dimension (mm): 54

# DELTALIGHT

## SPM20 - SPY 522 AIR 92720

29815 9220 B




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

2(2) | 1(0) | 1(0)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

1 | 1 | 1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

1 | - | -

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1/2 | 1/2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

1 | 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1 | 1 | 1/2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



**21012 0308** LED POWER SUPPLY 350mA / 7,35W DIM8

1/2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




**21012 0318** LED POWER SUPPLY 500mA / 10W DIM8

1/2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




**21012 0328** LED POWER SUPPLY 700mA / 15W DIM8

1/2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40



**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

1(1)


Dimtype: non-dimmable

Cutout dimension (mm): 60

# DELTALIGHT

## SPM20 - SPY 522 AIR 92720

29815 9220 B




**21012 0490** LED POWER SUPPLY 700mA-DC / 30W IP68

1(1/2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

1(1/2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

**Dimtype: DALI**

**Cutout dimension (mm): 30**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1

**Dimtype: DALI**

**Cutout dimension (mm): 30**




**21032 0315** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

1


**Dimtype: DALI**

**Cutout dimension (mm): 30**


### Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B



**19810 0020** LINEAR SPREAD LENS 42



**19810 0030** SPREAD LENS 42




**19810 0040** SOFTENING LENS 42


# DELTALIGHT

## SPM20 - SPY 522 AIR 92720

29815 9220 B




**19810 0050** GLASS SBL 42



**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

### Finish your product



**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

Notes: