
DELTALIGHT




POLESANO 930 SPOT

REFERENCE 43 11 931 A-B

AVAILABLE IN
ALU GREY-BLACK 43 11 931 A-B
ANTHRACITE-BLACK 43 11 931 N-B





View on website

General info	
LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP66
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	5
ADJUSTABILITY	360° swiveling, 360° rotatable
INFORMATION	16 x LENS SP-15° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC λ > 0,9 Inrush current : 32A - 355µs @ 230V-AC Max. 10 units on circuit breaker B 16A @ 230V-AC (13 units on B 20A)

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, ENEC+, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 41,6W / CRI>90 (R9: 60) / 3000K / 4718lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	4718lm // 41,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	3751lm // 48W // 78lm/W

Remarks

Take a look at the POLESANO brochure

Requirements

POLESANO POLE

Accessories

HONEYCOMB S105
LINEAR SPREAD LENS S105

DELTALIGHT

POLESANO 930 SPOT

43 11 931 A-B


For detailed installation instructions, please consult the manual : **43_XX_XXX-431_X00_XX1_(X)X1_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices




431 03 01 B HONEYCOMB S105 B ☐




431 03 02 LINEAR SPREAD LENS S105 ☐

Pole




431 400 111 11 A POLESANO 4M - 1 ANCHORED A ☐

431 400 111 11 N POLESANO 4M - 1 ANCHORED N ☐



431 400 111 21 A POLESANO 4M - 2 ANCHORED A ☐

431 400 111 21 N POLESANO 4M - 2 ANCHORED N ☐










431 400 111 31 A POLESANO 4M - 3 ANCHORED A ☐

431 400 111 31 N POLESANO 4M - 3 ANCHORED N ☐

DELTALIGHT







POLESANO 930 SPOT

43 11 931 A-B

	**431 400 111 41 A**	POLESANO 4M - 4 ANCHORED A
	431 400 111 41 N	POLESANO 4M - 4 ANCHORED N
	**431 400 111 211 A**	POLESANO 4M - 21L ANCHORED A
	431 400 111 211 N	POLESANO 4M - 21L ANCHORED N
	**431 400 111 221 A**	POLESANO 4M - 22L ANCHORED A
	431 400 111 221 N	POLESANO 4M - 22L ANCHORED N
	**431 400 221 11 A**	POLESANO 4M - 1 BASE A
	431 400 221 11 N	POLESANO 4M - 1 BASE N
	**431 400 221 21 A**	POLESANO 4M - 2 BASE A
	431 400 221 21 N	POLESANO 4M - 2 BASE N
	**431 400 221 31 A**	POLESANO 4M - 3 BASE A
	431 400 221 31 N	POLESANO 4M - 3 BASE N
	**431 400 221 41 A**	POLESANO 4M - 4 BASE A

POLESANO 930 SPOT


43 11 931 A-B

	431 400 221 41 N POLESANO 4M - 4 BASE N	☐
	**431 400 221 211 A** POLESANO 4M - 21L BASE A	☐
	431 400 221 211 N POLESANO 4M - 21L BASE N	☐
	**431 400 221 221 A** POLESANO 4M - 22L BASE A	☐
	431 400 221 221 N POLESANO 4M - 22L BASE N	☐
	**431 600 121 11 A** POLESANO 6M - 1 ANCHORED A	☐
	431 600 121 11 N POLESANO 6M - 1 ANCHORED N	☐
	**431 600 121 21 A** POLESANO 6M - 2 ANCHORED A	☐
	431 600 121 21 N POLESANO 6M - 2 ANCHORED N	☐
	**431 600 121 31 A** POLESANO 6M - 3 ANCHORED A	☐
	431 600 121 31 N POLESANO 6M - 3 ANCHORED N	☐
	**431 600 121 41 A** POLESANO 6M - 4 ANCHORED A	☐
	431 600 121 41 N POLESANO 6M - 4 ANCHORED N	☐

DELTALIGHT


POLESANO 930 SPOT

43 11 931 A-B




431 600 121 211 A POLESANO 6M - 21L ANCHORED A

431 600 121 211 N POLESANO 6M - 21L ANCHORED N




431 600 121 221 A POLESANO 6M - 22L ANCHORED A

431 600 121 221 N POLESANO 6M - 22L ANCHORED N




431 600 321 11 A POLESANO 6M - 1 BASE A

431 600 321 11 N POLESANO 6M - 1 BASE N




431 600 321 21 A POLESANO 6M - 2 BASE A

431 600 321 21 N POLESANO 6M - 2 BASE N




431 600 321 31 A POLESANO 6M - 3 BASE A

431 600 321 31 N POLESANO 6M - 3 BASE N



431 600 321 41 A POLESANO 6M - 4 BASE A

431 600 321 41 N POLESANO 6M - 4 BASE N




431 600 321 211 A POLESANO 6M - 21L BASE A

DELTALIGHT

POLESANO 930 SPOT

43 11 931 A-B

	431 600 321 211 N POLESANO 6M - 21L BASE N	☐
	**431 600 321 221 A** POLESANO 6M - 22L BASE A	☐
	431 600 321 221 N POLESANO 6M - 22L BASE N	☐

Notes: