



OML50 - LED ARRAY DU HO 1640mm 940

31035 9400



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.8
INFO	CLUSTER DOWN: 4029lm/m CLUSTER UP: 2776lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 40,8W / CRI>90 (R9: 50) / 4000K / 6608lm UP: LED cluster 30,2W / CRI>90 (R9: 50) / 4000K / 4552lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 6608lm // 40,8W // 162lm/W UP: 4552lm // 30,2W // 151lm/W

Notes: