
DELTALIGHT




# SUPERLOOP-SPY FOCUS MP 927 MDL

**REFERENCE** 20546 9200 B

AVAILABLE IN
**BLACK** 20546 9200 B
**FLEMISH BRONZE** 20546 9200 FBR
**FLEMISH GOLD** 20546 9200 FG




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | ADJUSTABLE BEAM 12°-45°<br>INCL.CLIP 48V ADAPTER<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, EAC, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 17,2W / CRI>90 (R9: 60) / 2700K / 2009lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 12°-45° |
| **LED TECHNICS (LIGHT SOURCE)** | 2009lm // 17,2W // 117lm/W |
| **LED TECHNICS (LUMINAIRE)** | 703lm // 19,8W // 36lm/W |

**Requirements**

LED POWER SUPPLY 48V-DC

**Options**

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **20546_9X00_HAND.pdf**

# SUPERLOOP-SPY FOCUS MP 927 MDL

20546 9200 B


## FINISH YOUR SPECIFICATION

### SMART 48

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 9

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 9


**Dimtype: WDL = wireless dimmable**

### LED power supplies

**# of Fixtures**

**Min current | Max current**


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 89 48 90** LED POWER SUPPLY 48V-DC / 90W — 5


**Dimtype: non-dimmable**

**Cutout dimension (mm): 75**





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 5

**Dimtype: non-dimmable**




**300 89 48 150** LED POWER SUPPLY 48V-DC / 150W — 7

**Dimtype: non-dimmable**





**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 12

**Dimtype: non-dimmable**

# SUPERLOOP-SPY FOCUS MP 927 MDL


20546 9200 B




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 5

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 10


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**


## COMPATIBLE COMPOSABLES

### SUPERLOOP HC MDL


Available Colours





**418 481 07** SUPERLOOP HC 70 MDL




**418 481 09** SUPERLOOP HC 90 MDL





**418 481 12** SUPERLOOP HC 120 MDL





**418 481 17** SUPERLOOP HC 170 MDL

### SUPERLOOP HC MDL XL

Available Colours





**20555 0000** SUPERLOOP HC 200 MDL





**20556 0000** SUPERLOOP HC 250 MDL

# SUPERLOOP-SPY FOCUS MP 927 MDL


20546 9200 B





**20557 0000** SUPERLOOP HC 300 MDL




**20558 0000** SUPERLOOP HC 350 MDL





**20559 0000** SUPERLOOP HC 400 MDL





**20560 0000** SUPERLOOP HC 500 MDL

## SUPERLOOP PLUS MDL


Available Colours




**20564 0000** SUPERLOOP PLUS HC 70 MDL





**20565 0000** SUPERLOOP PLUS HC 90 MDL





**20566 0000** SUPERLOOP PLUS HC 120 MDL

## SUPERLOOP S HC MDL

Available Colours




**418 482 106** SUPERLOOP S HC 106 MDL





**418 482 109** SUPERLOOP S HC 109 MDL


DELTALIGHT

# SUPERLOOP-SPY FOCUS MP 927 MDL

20546 9200 B




**418 482 211** SUPERLOOP S HC 211 MDL




**418 482 217** SUPERLOOP S HC 217 MDL

Notes: