





WANT-IT L 927 DIM8

275 13 82 92 ED8 B-FG

AVAILABLE IN

BLACK-FLEMISH GOLD 275 13 82 92 ED8 B-FG

WHITE-WHITE 275 13 82 92 ED8 W-W



 [View on website](#)



General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Wall Surface mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.5 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | INCL.DIMMABLE LED POWER SUPPLY 350mA-DC |

Electrical info

| | |
|---------------------|-----------------------|
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | II |
| POWER SUPPLY | YES |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | F |
| CERTIFICATES | CB, ENEC, LCA, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | 2 x (LED array 3,2W / CRI>90 (R9: 60) / 2700K / 297lm) |
| TM-30 VALUES | rf: 89 / Rg: 100 |
| SDCM | SDCM2 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 594lm // 6,4W // 94lm/W |
| LED TECHNICS (LUMINAIRE) | 221lm // 7,4W // 30lm/W |

For detailed installation instructions, please consult the manual : [275_13_82_XX_ED8_HAND.pdf](#)


DELTALIGHT

WANT-IT L 927 DIM8

275 13 82 92 ED8 B-FG

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Notes: