



M20/M26H - SPY 52 93020 DIM5

23324 9325 B

AVAILABLE IN

BLACK 23324 9325 B

FLEMISH BRONZE 23324 9325 FBR

FLEMISH GOLD 23324 9325 FG

GOLD COLOURED 23324 9325 GC

WHITE 23324 9325 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLLED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1467lm // 12,4W // 118lm/W
LED TECHNICS (LUMINAIRE)	919lm // 14,3W // 64lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42

SOFTENING LENS 42

GLASS SBL 42

DELTALIGHT

M20/M26H - SPY 52 93020 DIM5

23324 9325 B

For detailed installation instructions, please consult the manual : [23324_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

7

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

16

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

7

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

14

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B



19810 0020 LINEAR SPREAD LENS 42

DELTALIGHT

M20/M26H - SPY 52 93020 DIM5


23324 9325 B




19810 0030 SPREAD LENS 42

☐

19810 0040 SOFTENING LENS 42

☐


19810 0050 GLASS SBL 42

☐

19810 0060 B HONEYCOMB 42 DOUBLE USE B

☐

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

19810 0100 FG SPY 52 TUBE FG

☐


19810 0100 GC SPY 52 TUBE GC

☐

19810 0100 W SPY 52 TUBE W

☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

DELTALIGHT

M20/M26H - SPY 52 93020 DIM5

23324 9325 B



19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°



COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL

Available Colours



30411 9205 SHIFTLINE M26H + SBL 2m DIM5




30411 9305 SHIFTLINE M26H + SBL 2m DIM5




30412 9205 SHIFTLINE M26H + SBL 3m DIM5



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5



30413 9305 SHIFTLINE M26H + SBL 4m DIM5



DELTALIGHT

M20/M26H - SPY 52 93020 DIM5

23324 9325 B

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	
	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	
	23359 0030 SLM26H - PROFILE 3m	


SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	
	23397 0020 SPM20 ST - PROFILE 2m	
	23397 0030 SPM20 ST - PROFILE 3m	

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	

DELTALIGHT

M20/M26H - SPY 52 93020 DIM5

23324 9325 B



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: