
DELTALIGHT




M20/M26H - SPY 52 93020 DIM5

REFERENCE 23324 9325 B

AVAILABLE IN
BLACK 23324 9325 B
FLEMISH BRONZE 23324 9325 FBR
FLEMISH GOLD 23324 9325 FG
GOLD COLOURED 23324 9325 GC
WHITE 23324 9325 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1467lm // 12,4W // 118lm/W
LED TECHNICS (LUMINAIRE)	919lm // 14,3W // 64lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT

M20/M26H - SPY 52 93020 DIM5

23324 9325 B

For detailed installation instructions, please consult the manual : **23324_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7 ☐

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 16 ☐


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 14 ☐


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices




19810 0010 B HONEYCOMB 42 SINGLE USE B — ☐



19810 0020 LINEAR SPREAD LENS 42 — ☐

M20/M26H - SPY 52 93020 DIM5


23324 9325 B




19810 0030 SPREAD LENS 42



19810 0040 SOFTENING LENS 42




19810 0050 GLASS SBL 42



19810 0060 B HONEYCOMB 42 DOUBLE USE B

Finish your product



19810 0100 B SPY 52 TUBE B


19810 0100 FBR SPY 52 TUBE FBR

19810 0100 FG SPY 52 TUBE FG

19810 0100 GC SPY 52 TUBE GC

19810 0100 W SPY 52 TUBE W

Replaceable reflector / lens




19810 0180 SPY 52 REFLECTOR 20°

M20/M26H - SPY 52 93020 DIM5

23324 9325 B







19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL	Available Colours
 **30411 9205** SHIFTLINE M26H + SBL 2m DIM5	
 **30411 9305** SHIFTLINE M26H + SBL 2m DIM5	
 **30412 9205** SHIFTLINE M26H + SBL 3m DIM5	
 **30412 9305** SHIFTLINE M26H + SBL 3m DIM5	
 **30413 9205** SHIFTLINE M26H + SBL 4m DIM5	
 **30413 9305** SHIFTLINE M26H + SBL 4m DIM5	


DELTALIGHT

M20/M26H - SPY 52 93020 DIM5


23324 9325 B

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE




23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m

SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m




420 20 20 00 SPM20 - PROFILE 2m


DELTALIGHT

M20/M26H - SPY 52 93020 DIM5

23324 9325 B



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B

Notes: