





M26L - OCTAV 27 92730 DIM5

29015 9225 FBR

AVAILABLE IN
BLACK 29015 9225 B
FLEMISH BRONZE 29015 9225 FBR
FLEMISH GOLD 29015 9225 FG
GOLD COLOURED 29015 9225 GC
WHITE 29015 9225 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 27 L TUBE B included
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	276lm // 6,7W // 41lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [29015_XXX5_HAND.pdf](#)

M26L - OCTAV 27 92730 DIM5

29015 9225 FBR

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
55 100 90 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN 15	Dimtype: non-dimmable	
63 114 125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN 36	Dimtype: non-dimmable	
17 298 30 21012 0230 LED POWER SUPPLY 48V-DC / 100W 15	Dimtype: non-dimmable Cutout dimension (mm): 40	
22 392 30 21012 0240 LED POWER SUPPLY 48V-DC / 200W 30	Dimtype: non-dimmable Cutout dimension (mm): 40	


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
32 26 23358 0000 SLM26L - PROFILE	
32 26 23358 0010 SLM26L - PROFILE 1m	
32 26 23358 0020 SLM26L - PROFILE 2m	

DELTALIGHT

M26L - OCTAV 27 92730 DIM5

29015 9225 FBR



23358 0030 SLM26L - PROFILE 3m



Notes: