



INFORM SQ P144-3 DOWN 94067

25511 9420 B-FG



AVAILABLE IN

BLACK-BLACK 25511 9420 B-B

BLACK-FLEMISH GOLD 25511 9420 B-FG

WHITE-BLACK 25511 9420 W-B

WHITE-WHITE 25511 9420 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 300/450mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 4000K / 1670-2416lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2416lm // 16,7W // 144lm/W
LED TECHNICS (LUMINAIRE)	2109lm // 19,2W // 110lm/W

Requirements

INFORM SQ POWERBOX 25W

INFORM SQ POWERBOX 35W DIM5

INFORM POWER SUPPLY 17W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : [25511_XXX0_HAND.pdf](#)

INFORM SQ P144-3 DOWN 94067

25511 9420 B-FG

FINISH YOUR SPECIFICATION


Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




25510 0030 B INFORM SQ POWERBOX 25W B

1

Dimtype: non-dimmable

25510 0030 W INFORM SQ POWERBOX 25W W

1



25510 0045 B INFORM SQ POWERBOX 35W DIM5 B

1

Dimtype: DALI

25510 0045 W INFORM SQ POWERBOX 35W DIM5 W

1


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0375 INFORM POWER SUPPLY 17W DIM5

1

Dimtype: DALI



25510 0420 INFORM POWER SUPPLY 17W

1

Dimtype: non-dimmable

Electric connection parts

of Fixtures




of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

INFORM SQ P144-3 DOWN 94067

25511 9420 B-FG



15225 0350 B SUSPENSION + CONNECTION ST B

2 needed

☐

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W

2 needed

☐

Notes: