



OML50 - LED ARRAY DU HO 1968mm 930 DIM5

31036 9305



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2,1
INFO	CLUSTER DOWN: 3863lm/m CLUSTER UP: 2663lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 49W / CRI>90 (R9: 50) / 3000K / 7603lm UP: LED cluster 36,3W / CRI>90 (R9: 50) / 3000K / 5242lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 7603lm // 49W // 155lm/W UP: 5242lm // 36,3W // 145lm/W

Opties

WIRELESS CONTROL DIM5

Notes: