




## OML50 - INFORM DU HE 984mm 24LED 93063

31440 9330 B

BESCHIKBAAR IN  
**ZWART** 31440 9330 B



[Bekijk op website](#)



### Algemene info

|                               |                                                                                             |
|-------------------------------|---------------------------------------------------------------------------------------------|
| <b>LOCATIE</b>                | binnen                                                                                      |
| <b>STOF EN WATERDICHTHEID</b> | IP20                                                                                        |
| <b>GEWICHT (KG)</b>           | 1                                                                                           |
| <b>INFO</b>                   | CLUSTER DOWN: 3863lm/m<br>CLUSTER UP: 1932lm/m<br>INCLLED POWER SUPPLY<br>CABLING 1 CIRCUIT |

### Elektrische info

|                           |                      |
|---------------------------|----------------------|
| <b>ELEKTRISCH</b>         | 220-240V / 0 50-60Hz |
| <b>KLASSE</b>             | I                    |
| <b>VOEDING INBEGREPEN</b> | YES                  |
| <b>DIM TYPE</b>           | niet dimbaar         |
| <b>ENERGIE KLASSE</b>     | D                    |
| <b>CERTIFICATES</b>       | EPD, RCM             |

### Info lichtbron

|                                 |                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>         | LED                                                                                                                    |
| <b>LICHTBRON</b>                | DOWN: LED cluster 24,5W / CRI>90 (R9: 50) / 3000K / 3802lm<br>UP: LED cluster 12,2W / CRI>90 (R9: 50) / 3000K / 1901lm |
| <b>TM-30 WAARDEN</b>            | Rf: 92 / Rg: 100                                                                                                       |
| <b>SMD</b>                      | SDCM3                                                                                                                  |
| <b>RISK-GROEP</b>               | RG1                                                                                                                    |
| <b>LM80</b>                     | L80 > 60000                                                                                                            |
| <b>BEAMANGLE</b>                | 63°                                                                                                                    |
| <b>LED TECHNIEK (LICHTBRON)</b> | DOWN: 3802lm // 24,5W // 155lm/W<br>UP: 1901lm // 12,2W // 155lm/W                                                     |

Notes: