DELTALIGHT

WANT-IT L 930 DIM8

275 13 82 93 ED8 B-FG

AVAILABLE IN
BLACK-FLEMISH GOLD 275 13 82 93 ED8 B-FG
WHITE-WHITE 275 13 82 93 ED8 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 3,2W / CRI>90 (R9: 52) / 3000K / 309lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	618lm // 6,4W // 98lm/W
LED TECHNICS (LUMINAIRE)	230lm // 7,4W // 31lm/W

For detailed installation instructions, please consult the manual : **275_13_82_XX_ED8_HAND.pdf**

DELTALIGHT

WANT-IT L 930 DIM8

275 13 82 93 ED8 B-FG

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Notes: