





HALOSCAN ST HP 93014

23114 9310 W

AVAILABLE IN
NOIR 23114 9310 B
BLANC 23114 9310 W



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 70
RECESSED DEPTH (MM)	55
THICKNESS OF MOUNTING SURFACE (MM)	min.1
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS SP-14° EXCL.LED POWER SUPPLY 350mA-DC
Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1239lm // 13,3W // 93lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Accessories

HALOSCAN HONEYCOMB
 HALOSCAN LINEAR SPREAD LENS


For detailed installation instructions, please consult the manual : [23114_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

les batteries de secours

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

les alimentations led

		# of Fixtures
 300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1		1 ☐
Dimtype: 1 à 10 V		
Cutout dimension (mm): 30		

HALOSCAN ST HP 93014

23114 9310 W



300 48 350 ED5


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1



Dimtype: DALI

Cutout dimension (mm): 45



300 48 350 MDL


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1



Dimtype: non dimmable

Cutout dimension (mm): 30



300 48 350 WDL


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1



Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 45



300 90 61


LED POWER SUPPLY MULTI-POWER DIM6

1



Dimtype: fin de phase ou bouton poussoir

Cutout dimension (mm): 56



300 90 63


LED POWER SUPPLY MULTI-POWER DIM9

2(2)



Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 82



300 90 64


LED POWER SUPPLY MULTI-POWER DIM7

1(1)



Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 72




300 90 67

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

1



Dimtype: 1 à 10 V ou DALI ou bouton poussoir



300 90 68


LED POWER SUPPLY MULTI-POWER DIM5

1(1)



Dimtype: DALI

Cutout dimension (mm): 72



300 90 69

LED POWER SUPPLY MULTI-POWER HV DIM9

3(3)



Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 84



300 90 124

LED POWER SUPPLY MULTI-POWER DIM7

1(1)







Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 55

HALOSCAN ST HP 93014


23114 9310 W

	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) ☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	2->2 ☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 ☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	2(2) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	1 ☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	1 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(1) ☐

DELTALIGHT

HALOSCAN ST HP 93014

23114 9310 W



21032 0295


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1 ☐

Dimtype: DALI

Cutout dimension (mm): 30


modifier les dispositifs de lumière



23110 0040

HALOSCAN LINEAR SPREAD LENS

☐



23110 0050 B

HALOSCAN HONEYCOMB B

☐

Notes: