
DELTALIGHT




M26L - SPY 391 SOFT 93020 MDL

REFERENCE 23437 9020 BRG

AVAILABLE IN
BLACK 23437 9020 B
BRUSHED ALU 23437 9020 BRA
BRUSHED ANTHRACITE 23437 9020 BRAT
BRUSHED COPPER 23437 9020 BRCU
BRUSHED GOLD 23437 9020 BRG
BRUSHED OLD BRONZE 23437 9020 BROB
FLEMISH BRONZE 23437 9020 FBR
FLEMISH GOLD 23437 9020 FG
GOLD COLOURED 23437 9020 GC
PIANO BLACK 23437 9020 PB
WHITE 23437 9020 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL

23437 9020 BRG

For detailed installation instructions, please consult the manual : **23437_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 16


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 16


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 8

Dimtype: non-dimmable

DELTALIGHT


M26L - SPY 391 SOFT 93020 MDL

23437 9020 BRG



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 20


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 8

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 17

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR

24144 0010 FG SPY 39 TUBE FG

24144 0010 GC SPY 39 TUBE GC


24144 0010 W SPY 39 TUBE W



24144 0070 SPY 39 TUBE SBL

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX) — **Available Colours**




23358 0000 SLM26L - PROFILE

DELTALIGHT


M26L - SPY 391 SOFT 93020 MDL

23437 9020 BRG




23358 0010 SLM26L - PROFILE 1m





23358 0020 SLM26L - PROFILE 2m





23358 0030 SLM26L - PROFILE 3m



Notes: