





SUPERNOVA LINE 125 930

20626 9300 B

AVAILABLE IN

BLACK 20626 9300 B

WHITE 20626 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	19.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 235,2W / CRI>90 (R9: 50) / 3000K / 3454lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3454lm // 235,2W // 147lm/W
LED TECHNICS (LUMINAIRE)	26527lm // 270,5W // 98lm/W

Options

SUSPENSION SET 18 3m

CABLE BASE R / S


COVERSET R 62-90-100 / S 62-80-90

SUPERNOVA 125 RECESSED KIT

For detailed installation instructions, please consult the manual : [20626_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



41 **203 99 55 ANO** CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

41 **203 99 56 ANO** CABLE BASE S ANO

☐

203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Recessed kits




115 **274 94 1310** SUPERNOVA 125 RECESSED KIT

☐

Cutout dimension (mm): 1335

Coversets



204 00 62 ANO COVERSET R 62 ANO

☐

204 00 62 B COVERSET R 62 B

☐






204 00 62 W COVERSET R 62 W

☐

DELTALIGHT

SUPERNOVA LINE 125 930

20626 9300 B



	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐
	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA LINE 125 930

20626 9300 B

Suspension parts

	<u>328 18 43</u>	SUSPENSION SET 18 3m	☐
	<u>328 24 61 B</u>	CENTRAL ROD SUSPENSION 65 1m B	☐
	<u>328 24 61 W</u>	CENTRAL ROD SUSPENSION 65 1m W	☐
	<u>328 24 91 B</u>	CENTRAL ROD SUSPENSION 95 1m B	☐
	<u>328 24 91 W</u>	CENTRAL ROD SUSPENSION 95 1m W	☐

Electric connection parts

	<u>15225 0360 B</u>	CONNECTION ST B	☐
		Cutout dimension (mm): 43	
	<u>15225 0360 W</u>	CONNECTION ST W	☐

Notes: