
DELTALIGHT




# SPY 52 93020 ADM SLIM

**REFERENCE** 19836 9320 W

AVAILABLE IN
**BLACK** 19836 9320 B
**WHITE** 19836 9320 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Mains voltage track Mains voltage track mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 360° rotatable |
| **INFORMATION** | REFLECTOR FL-20°<br>3F MULTI POWER SLIM ADAPTER 350-700mA<br>Current selection via jumper on adapter<br>Optional REFLECTORS 30° & 45° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 50-60Hz |
| **CLASS** | II |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | non-dimmable |
| **ENERGY CLASS** | D |
| **CERTIFICATES** | CB, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | @ 700mA: LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm<br>Or<br>@ 500mA: LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm<br>Or<br>@ 350mA: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| **TM-30 VALUES** | @ 700mA: Rf: 90 / Rg: 99<br>@ 500mA: Rf: 90 / Rg: 99<br>@ 350mA: Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | @ 700mA: 1467lm // 12,4W // 118lm/W<br>Or<br>@ 500mA: 1089lm // 8,6W // 127lm/W<br>Or<br>@ 350mA: 787lm // 5,8W // 135lm/W |
| **LED TECHNICS (LUMINAIRE)** | @ 700mA: 919lm // 14W // 64lm/W<br>Or<br>@ 500mA: 682lm // 10W // 69lm/W<br>Or<br>@ 350mA: 493lm // 7W // 74lm/W |

DELTALIGHT

# SPY 52 93020 ADM SLIM

19836 9320 W

**Requirements**

SPY 52 TUBE
TRACK 3F DIM


**Accessories**

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42


For detailed installation instructions, please consult the manual : **19836_XXX0_HAND.pdf**

## FINISH YOUR SPECIFICATION


### Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B ☐





**19810 0020** LINEAR SPREAD LENS 42 ☐





**19810 0030** SPREAD LENS 42 ☐




**19810 0040** SOFTENING LENS 42 ☐




**19810 0050** GLASS SBL 42 ☐




**19810 0060 B** HONEYCOMB 42 DOUBLE USE B ☐

# SPY 52 93020 ADM SLIM

19836 9320 W

## Finish your product




**19810 0100 B** SPY 52 TUBE B


**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG


**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W


## Replaceable reflector / lens




**19810 0180** SPY 52 REFLECTOR 20°




**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°

## COMPATIBLE TRACKS

| TRACK 3F DIM H | | | Available Colours |
|---|---|---|---|
| **200 14 410** TRACK 3F DIM H 1m | 1000 m | 1.6 kg | |
| **200 14 420** TRACK 3F DIM H 2m | 2000 m | 3.2 kg | |
| **200 14 430** TRACK 3F DIM H 3m | 3000 m | 4.8 kg | |

| TRACK 3F DIM IN | | | Available Colours |
|---|---|---|---|
| **200 13 410** TRACK 3F DIM IN 1m | 1000 m | 1.2 kg | |

DELTALIGHT

## SPY 52 93020 ADM SLIM

19836 9320 W

| | | | |
|---|---|---|---|
| **200 13 420** TRACK 3F DIM IN 2m | 2000 m | 2.4 kg | |
| **200 13 430** TRACK 3F DIM IN 3m | 3000 m | 3.5 kg | |

| **TRACK 3F DIM ON** | | | **Available Colours** |
|---|---|---|---|
| **200 12 410** TRACK 3F DIM ON 1m | 1000 m | 1.1 kg | |
| **200 12 420** TRACK 3F DIM ON 2m | 2000 m | 2.1 kg | |
| **200 12 430** TRACK 3F DIM ON 3m | 3000 m | 3.1 kg | |

Notes: