





D-LINER 19 INF LOC1 286 93058
DIM5

32012 9325 B

AVAILABLE IN
BLACK 32012 9325 B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	12 x REFLECTOR 58° INCL.DIMMABLE LED POWER SUPPLY 150mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 0,5m + WIELAND PLUG GST18i5 male pastelblue
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4,3-5W / CRI>90 / 3000K / 764-877lm
BEAMANGLE	58°
LED TECHNICS (LIGHT SOURCE)	877lm // 5W // 174lm/W
LED TECHNICS (LUMINAIRE)	746lm // 5,8W // 130lm/W

For detailed installation instructions, please consult the manual : [32012_XXX5_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-

DELTALIGHT

D-LINER 19 INF LOC1 286 93058 DIM5

32012 9325 B



Acoustic climate-control ceiling Hunter Douglas 30BD

Notes: