





MIKALINE L198 930

30612 9300 B

AVAILABLE IN
BLACK 30612 9300 B
GOLD COLOURED 30612 9300 GC



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PLUG-IN-48V CABLE 11cm black EXCL.LED POWER SUPPLY 48V-DC connection max.140W (3A)

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LEDFLEX 27W / CRI>90 / 3000K /2138lm
LED TECHNICS (LIGHT SOURCE)	2138lm // 27W // 79lm/W
LED TECHNICS (LUMINAIRE)	1125lm // 31W // 36lm/W




Requirements	
LED POWER SUPPLY 48V-DC (Remote)	
POWERBOX 48V-DC PLUG-IN	

Options	
MIKALINE - JUNCTION / FIXATION	
MIKALINE - CABLE SUSPENSION	
PLUG-IN 48V CABLE	
CONNECTION CLIP 1 x PLUG-IN 48V	
CEILING BASE PLUG-IN 48V	





For detailed installation instructions, please consult the manual : [30612_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	30610 0100 PLUG-IN 48V CABLE 11cm black	☐
	30610 0110 PLUG-IN 48V CABLE 1,5m black	☐
	30610 0120 PLUG-IN 48V CABLE 3m black	☐
	30610 0140 B CONNECTION CLIP 1 x PLUG-IN 48V B	☐
Cutout dimension (mm): 51		




LED power supplies

	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	☐
Dimtype: non-dimmable		
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	☐
Dimtype: non-dimmable		
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		


DELTALIGHT

MIKALINE L198 930

30612 9300 B

	21032 0331 LED POWER SUPPLY 48V-DC / 90W DIM1	☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 75	
	21032 0345 LED POWER SUPPLY 48V-DC / 90W DIM5	☐
	Dimtype: DALI	
	Cutout dimension (mm): 75	
	30610 0190 POWER ADAPTER 48V-DC / 60W PLUG-IN	☐
	Dimtype: non-dimmable	

Power box

	30610 0170 B POWERBOX 48V-DC / 100W PLUG-IN B	☐
	Dimtype: non-dimmable	

Suspension parts

	30610 0080 B MIKALINE - CABLE SUSPENSION SINGLE 1,6m B	☐
---	---	--------------------------


Fixation components

	30610 0010 C MIKALINE - JUNCTION 2 FLEX SET C	☐
	30610 0020 C MIKALINE - JUNCTION 3 FLEX C	☐

DELTALIGHT

MIKALINE L198 930

30612 9300 B

	30610 0030 C MIKALINE - JUNCTION 4 FLEX C	☐
	30610 0040 C MIKALINE - JUNCTION 2 HINGE C	☐
	30610 0050 C MIKALINE - FIXATION SIDE SET C	☐
	30610 0060 B MIKALINE - FIXATION SPACER FLEX SET B	☐
	30610 0070 C MIKALINE - FIXATION H/V FLEX C	☐
	30610 0090 B MIKALINE - FIXATION SPACER SET B	☐
	30610 0180 B MIKALINE - SPACER 90° 2 SET B	☐

Ceiling bases

	30610 0150 B CEILING BASE 3 x PLUG-IN 48V B	☐
	30610 0160 B CEILING BASE 1 x PLUG-IN 48V B	☐

DELTALIGHT

MIKALINE L198 930

30612 9300 B

Notes: