
DELTALIGHT




SPLIT-IT SPY 66 92730

REFERENCE 18434 9220 W

AVAILABLE IN
BLACK 18434 9220 B
WHITE 18434 9220 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
INFORMATION	ADJUSTABLE REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC EXCL.LED POWER CONVERTER 48V TO 500mA-DC PRO Optional REFLECTORS 18° & 45° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-17,2W / CRI>90 (R9: 60) / 2700K / 1458-2009lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	1384lm // 19,8W // 70lm/W

Requirements

SPY 66 TUBE
LED POWER CONVERTER 48V-DC to 500 mA-DC
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING 48V-DC

Accessories

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

DELTALIGHT


SPLIT-IT SPY 66 92730

18434 9220 W

For detailed installation instructions, please consult the manual : **18434_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply




416 99 00 THROUGH WIRING 48V-DC SPLIT-IT PRO ☐

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 500 PRO ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM1 1 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 500 PRO ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM5 1 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 500 PRO WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO WDL 1 ☐

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 1 | 1 ☐

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 2(2) | 2(2) ☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82

SPLIT-IT SPY 66 92730


18434 9220 W



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 1(1) | 1(0)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 1 | -


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 1(1) | 1(0)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 3(3) | 3(2)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 1(1) | 1(0)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 1(1) | 1(0)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 2->2 | 2

Dimtype: non-dimmable


Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 1 | 1

Dimtype: non-dimmable


Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 1 | 1

Dimtype: 1-10V

Cutout dimension (mm): 54




21012 0035 LED POWER SUPPLY MULTI POWER DIM5 1 | 1

Dimtype: DALI

Cutout dimension (mm): 54

SPLIT-IT SPY 66 92730


18434 9220 W



21012 004W LED POWER SUPPLY MULTI-POWER WDL 2(2) | 2(2)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 1 | 1

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 1 | 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 1(1)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21032 0375 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM5 1

Dimtype: DALI

Cutout dimension (mm): 30

Light altering devices




24611 0150 B HONEYCOMB 57 SINGLE USE B

SPLIT-IT SPY 66 92730


18434 9220 W




24611 0160 GLASS SBL 57




24611 0170 LINEAR SPREAD LENS 57



24611 0190 SOFTENING LENS 57




24611 0200 SPREAD LENS 57



24611 0210 B HONEYCOMB 57 DOUBLE USE B

Finish your product



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

DELTALIGHT

SPLIT-IT SPY 66 92730

18434 9220 W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°




24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°

COMPATIBLE COMPOSABLES

SPLIT-IT PRO profile	Available Colours
 **372 01 00** SPT PRO - PROFILE	

Notes: