



OML50 - INFORM DU HE 984mm 24LED 93063 DIM5

31440 9335 B

AVAILABLE IN
BLACK 31440 9335 B



[View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 1.5 |
| INFORMATION | CLUSTER DOWN: 3863lm/m CLUSTER UP: 1932lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |

Electrical info

| | |
|---------------------|----------------------|
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI |
| ENERGY CLASS | D |
| CERTIFICATES | EPD, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | DOWN: LED cluster 24,5W / CRI>90 (R9: 50) / 3000K / 3802lm UP: LED cluster 12,2W / CRI>90 (R9: 50) / 3000K / 1901lm |
| TM-30 VALUES | Rf: 92 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUPE | RG1 |
| LM80 | L80 > 60000 |
| BEAMANGLE | 63° |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 3802lm // 24,5W // 155lm/W UP: 1901lm // 12,2W // 155lm/W |

Options

WIRELESS CONTROL DIM5

Notes: