




D-LINER 19 INF LOC1 286 94058 DIM5

32012 9425 B

AVAILABLE IN
BLACK 32012 9425 B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	12 x REFLECTOR 58° INCL.DIMMABLE LED POWER SUPPLY 150mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 0,5m + WIELAND PLUG GST18i5 male pastelblue
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5W / CRI>90 / 4000K / 904lm
BEAMANGLE	58°
LED TECHNICS (LIGHT SOURCE)	904lm // 5W // 180lm/W
LED TECHNICS (LUMINAIRE)	769lm // 5,8W // 134lm/W

For detailed installation instructions, please consult the manual : [32012_XXX5_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Interlu SAPP

-

D-LINER 19 INF LOC1 286 94058 DIM5

32012 9425 B



Acoustic climate-control ceiling Hunter Douglas 30BD

Notes: