# SPY S



Despite its minimalistic appearance, Spy S wows you with its powerful and striking light effect. As a surface module, its slenderness allows you to create playful or humble set-ups by grouping multiple luminaires or choosing just one single point of light.

Specification	
LED Aperture:	25/16"
Installation Method:	4" J-Box
Adjustability:	Fixed
Rating:	IP20

Performance		
LED Maintenance:	L70>50,000h	
McAdam Step:	2	
CRI:	90	
*SP:	10.4W	

Delivered Lumens	2700K	3000K	3500K		
Optic:	33°	33°	33°		
Spy S:	557Lm	580Lm	598Lm		

## Listing

ETL certified to US and Canadian safety standards.

#### Warranty

5-year limited warranty.

# Ordering ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SPY63SF-SP3330F-B-FG-INCD8-120

Luminaire	Size	Installation	Power*	Optic	ССТ	Function	Finish	Inner Finish	Application	Controls***
SPY SPY	63 63mm / 2 <sup>1</sup> / <sub>2</sub> " Diameter	SF Surface Mount	SP Standard Power	<b>33</b> 33°	27 2700K 30 3000K 35 3500K	F Fixed	B Black W White	B Black FBR Flemish Bronze FG Flemish Gold MMAT Gold Matte SG Silver Grey W White	INC Integral Power Supply	<b>D8-120</b> FE ELV dim 120V

\*\*\* Contact factory for additional dimming options.

# **Finish Options**

# SPY S







# **Related Products**

Spy 27, Spy 39, Spy 52, Spy 66, Spy 90, Spy Focus, Spy C (pendant), Superloop-Spy MDL



# Finish Options (cont'd)

## **INNER FINISH**















# **Accessories**







HONEYCOMB 50 413 03 01 B



LINEAR SPREAD LENS 50 413 03 02




SOFTENING LENS 50 413 03 04



SPREAD LENS 50 413 03 03

# **Photometric Data**

# SPY S



# **Driver Options**

Efficiency @ Full Load

THD @ Full Load

#### D8

Dimming Control
 Dimming Range
 Dim to off
 Power Factor @ Full Load
 >0.9

≥80

<5%

### **Dimmer Compatibility**

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

