SPY S



Despite its minimalistic appearance, Spy S wows you with its powerful and striking light effect. As a surface module, its slenderness allows you to create playful or humble set-ups by grouping multiple luminaires or choosing just one single point of light.

Specification	
LED Aperture	$2^{5}/_{16}$"
Installation Method:	4" junction box
Adjustability:	Fixed
Rating:	Damp (EU IP20)

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
McAdam Step:	1
LED Maintenance:	L90B10>50,000h
*Standard Power:	10.4W

Delivered Lumens	2700K	3000K	3500K
**Optic:	MD	MD	MD
Spy S:	557	580	598

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SPY63-F30MDSP-B-FG-ONPRINCD8-120

Luminaire	Size	Function	CCT	Optic**	Power*	Finish	Inner Finish	Type	Installation	Application	Controls***
SPY SPY S	**63** 63mm / $2^{1}/_{2}$" Diameter	**F** Fixed	**27** 2700K **30** 3000K **35** 3500K	**MD** Medium Spot 33°	**SP** Standard Power	**B** Black **W** White	**B** Black **FBR** Flemish Bronze **FG** Flemish Gold **MMAT** Gold Matte **SG** Silver Grey **W** White	**ON** Surface Mount	**PR** Integrated round coverplate for 4" junction box (matches selected Finish)	**INC** Integral Power Supply	**D8-120** FE ELV dim 120V


*** Contact factory for additional dimming options.

Related Products

Spy 27, Spy 39, Spy 52, Spy 66, Spy 90, Spy Focus, Spy C (pendant), Superloop-Spy MDL

Finish Options


SPY S





BLACK


WHITE

INNER FINISH




BLACK


FLEMISH BRONZE


FLEMISH GOLD



GOLD MATTE


SILVER GREY



WHITE

Accessories


GLASS SBL 50
413 03 05


HONEYCOMB 50
413 03 01 B


LINEAR SPREAD LENS 50
413 03 02


SOFTENING LENS 50
413 03 04


SPREAD LENS 50
413 03 03


SBL
LIGHT EFFECT


HONEYCOMB
LIGHT EFFECT



LINEAR SPREAD LENS
LIGHT EFFECT


SOFTENING LENS
LIGHT EFFECT


SPREAD LENS
LIGHT EFFECT

Photometric Data

SPY S



MD 33*

Driver Options

D8

- Dimming Control: Phase Control
- Dimming Range: 10-100%
- Dim to off: no
- Power Factor @ Full Load: >0.9
- Efficiency @ Full Load: ≥80
- THD @ Full Load: <5%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.