





D-LINER 19 INF LOC1 562 93058 DIM5

32014 9325 B

AVAILABLE IN
BLACK 32014 9325 B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	24 x REFLECTOR 58° INCL.DIMMABLE LED POWER SUPPLY 260mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 0,5m + WIELAND PLUG GST18i5 male pastelblue

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 8,6W / CRI>90 / 3000K / 1529lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	58°
LED TECHNICS (LIGHT SOURCE)	1529lm // 8,6W // 177lm/W
LED TECHNICS (LUMINAIRE)	1301lm // 9,9W // 132lm/W

For detailed installation instructions, please consult the manual : [32014_XXX5_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interalu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

Notes: