
DELTALIGHT




MICROGRID IN 3 93030

REFERENCE 100059 9320 B-W

AVAILABLE IN
BLACK-BLACK 100059 9320 B-B
BLACK-WHITE 100059 9320 B-W
WHITE-BLACK 100059 9320 W-B
WHITE-WHITE 100059 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 62 x 168
RECESSED DEPTH (MM)	75
THICKNESS OF MOUNTING SURFACE (MM)	min.12 - max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	INCL.3 x LENS FL-30° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm)
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1155lm // 11,7W // 98lm/W
LED TECHNICS (LUMINAIRE)	875lm // 13,5W // 65lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Accessories

MICRO VISOR

For detailed installation instructions, please consult the manual : **100059_XXX0_HAND.pdf**

DELTALIGHT

MICROGRID IN 3 93030

100059 9320 B-W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 1

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 1

Dimtype: DALI


Cutout dimension (mm): 45



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 1

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 1


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DELTALIGHT

MICROGRID IN 3 93030


100059 9320 B-W



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 1

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 2(2)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 1(1)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 1


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 1(1)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 3(3)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 1(1)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1(1)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV — 2->2

Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER — 1


Dimtype: non-dimmable

Cutout dimension (mm): 50

DELTALIGHT

MICROGRID IN 3 93030


100059 9320 B-W



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 — 1

Dimtype: 1-10V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 — 1

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL — 2(2)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 — 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 1(1)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 — 1(0)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 — 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 1

Dimtype: DALI


Cutout dimension (mm): 30

DELTALIGHT

MICROGRID IN 3 93030

100059 9320 B-W

Light altering devices



10034 0010 B MICRO VISOR B

Notes: