



MICROSPY IN TRIMLESS OK 92715

24112 9210 W

AVAILABLE IN
BLACK 24112 9210 B
WHITE 24112 9210 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	75
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	LENS SP-15° EXCL.LED POWER SUPPLY 350-450mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-5,1W / CRI>90 (R9: 56) / 2700K / 385-480lm
TM-30 VALUES	rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	480lm // 5,1W // 94lm/W
LED TECHNICS (LUMINAIRE)	360lm // 5,9W // 61lm/W

Requirements	
MOUNTING KIT TRIMLESS MICROSPY IN OK	
LED POWER SUPPLY 350 / 450mA-DC DIM (Remote)	

Accessories	
MICRO VISOR	

For detailed installation instructions, please consult the manual : [24112_XXXX_HAND.pdf](#)

MICROSPY IN TRIMLESS OK 92715

24112 9210 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK Required
 Plasterboard	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK Required
 Stucanet	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK Required
 Concrete + plaster	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK Required
 Lintel + plaster	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK Required
 Hollow-core slab + plaster	 15212 2020 - MOUNTING KIT TRIMLESS MICROSPY IN OK Required

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

Dimtype: 1-10V

Cutout dimension (mm): 30

3



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

Dimtype: DALI

Cutout dimension (mm): 45

3



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

Dimtype: non-dimmable

Cutout dimension (mm): 30

3



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

Dimtype: WDL = wireless dimmable











Cutout dimension (mm): 45

3

DELTALIGHT

MICROSPY IN TRIMLESS OK 92715











24112 9210 W

	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	3 - - ☐
Dimtype: mains (phase cut-off) or push button		
Cutout dimension (mm): 56		
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	6(6) - ☐
Dimtype: 1-10V or DALI or push button		
Cutout dimension (mm): 82		
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	4(3) - - ☐
Dimtype: 1-10V or push button		
Cutout dimension (mm): 72		
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	3 - - ☐
Dimtype: 1-10V or DALI or push button		
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	3(3) - - ☐
Dimtype: DALI		
Cutout dimension (mm): 72		
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->9(10) 2->9(4) ☐
Dimtype: 1-10V or DALI or push button		
Cutout dimension (mm): 84		
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W	3(2) ☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		
	300 90 108 LED POWER SUPPLY 350mA-DC / 8W	1 ☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		
	300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8	2->2 ☐
Dimtype: mains (phase cut-off)		
Cutout dimension (mm): 42		
	300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8	3->4 ☐
Dimtype: mains (phase cut-off)		
Cutout dimension (mm): 55		

DELTALIGHT

MICROSPY IN TRIMLESS OK 92715

24112 9210 W


	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	2->4(3) 3(2)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	4(3) 3(2)	☐
	300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 84	2->8(8) - -	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	4->6 - -	☐
	300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 43	2->3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	5(5) - -	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	4 -	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	3 3	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	4(3)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	3	☐

DELTALIGHT

MICROSPY IN TRIMLESS OK 92715

24112 9210 W

Mounting kits




15212 2020 MOUNTING KIT TRIMLESS MICROSPY IN OK



Cutout dimension (mm): 68

Light altering devices



10034 0010 B MICRO VISOR B



Notes: