

ENTERO SQ-S TRIMLESS WALLWASH TW 940



28565 9000 B

AVAILABLE IN

BLACK 28565 9000 B

GOLD COLOURED 28565 9000 GC

WHITE 28565 9000 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.145
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	801lm // 10,4W // 77lm/W

Requirements

MOUNTING KIT ENTERO SQUARE S

LED POWER SUPPLY 500mA-DC TW (Remote)


















For detailed installation instructions, please consult the manual : [28565_XXX0_HAND.pdf](#)

DELTALIGHT

ENTERO SQ-S TRIMLESS WALLWASH TW 940

28565 9000 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Plasterboard	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Stucanet	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Wood	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Concrete + plaster	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Lintel + plaster	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Hollow-core slab + plaster	 28400 0040 - MOUNTING KIT ENTERO SQ-S	Required
 Stretched ceiling	 28400 0160 - MOUNTING KIT ENTERO SQ-S WSC	Required
	 28400 0100 - MOUNTING KIT ENTERO SQ-S CSC	Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

2

Dimtype: DALI

Cutout dimension (mm): 85

Mounting kits



28400 0040 MOUNTING KIT ENTERO SQ-S


Cutout dimension (mm): 106 x 106

DELTALIGHT

ENTERO SQ-S TRIMLESS WALLWASH TW 940

28565 9000 B

Mounting kits stretched ceiling



28400 0100 MOUNTING KIT ENTERO SQ-S CSC



28400 0160 MOUNTING KIT ENTERO SQ-S WSC



Notes: