
DELTALIGHT




COMPO L IP44 94050

REFERENCE 9 15755 9440 DC

AVAILABLE IN
BLACK 9 15755 9440 B
CHROMED 9 15755 9440 C
DARK CHROMED 9 15755 9440 DC
WHITE 9 15755 9440 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.476
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 79) / 4000K / 2222lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	2222lm // 17,2W // 130lm/W
LED TECHNICS (LUMINAIRE)	1622lm // 20W // 82lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B
COMPO L LINEAR SPREAD LENS
COMPO L SPREAD LENS
COMPO L SOFTENING LENS
COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : **9_15755_XXX0_HAND.pdf**

DELTALIGHT

COMPO L IP44 94050

9 15755 9440 DC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
 Plasterboard	15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
 Wood	15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3200	LED POWER SUPPLY MULTIPOWER 15W NO DIM 300mA	1->2
15710 3600	LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA	1
15710 3700	LED POWER SUPPLY MULTIPOWER 10W DIM8 300mA	1
15710 4200	LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA	1
15710 4400	LED POWER SUPPLY MULTIPOWER 12W DIM1 300mA	1->2
15710 4700	LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA	1
15710 5200	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 300mA	1->2

Dimtype: DALI

15710 5400	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1


Dimtype: DALI

DELTALIGHT

COMPO L IP44 94050

9 15755 9440 DC

Mounting kits



15710 0030 B MOUNTING KIT COMPO L TRIM B ☐

Cutout dimension (mm): 92

15710 0030 W MOUNTING KIT COMPO L TRIM W ☐



15710 0060 MOUNTING KIT COMPO L TRIMLESS ☐

Cutout dimension (mm): 92

Light altering devices

15710 2100 B COMPO L HONEYCOMB SINGLE USE B ☐

15710 2110 COMPO L LINEAR SPREAD LENS ☐

Cutout dimension (mm): 42

15710 2120 COMPO L SPREAD LENS ☐

Cutout dimension (mm): 42

15710 2130 COMPO L SOFTENING LENS ☐

Cutout dimension (mm): 42

15710 2140 COMPO L GLASS SBL ☐

Cutout dimension (mm): 42

Notes: