




FRAX MB 92726 DIM5

26010 9265 FBRX

AVAILABLE IN
FLEMISH BRONZE OUTDOOR 26010 9265 FBRX
ANTHRACITE 26010 9265 N
PINE GREEN 26010 9265 PGR



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.1
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC INCL.BEAM LENS 26° INCL.1 x CABLE H05 RN-F 5 x 1mm² 2m

Electrical info

ELECTRICAL	110-277V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2423lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	26°
LED TECHNICS (LIGHT SOURCE)	2423lm // 23,4W // 103lm/W
LED TECHNICS (LUMINAIRE)	1745lm // 26,9W // 65lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP

For detailed installation instructions, please consult the manual : [26010_XX65_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Pins and plates for bollards

	26070 0040 FBRX FRAX PIN FBRX	☐
	26070 0040 N FRAX PIN N	☐
	26070 0040 PGR FRAX PIN PGR	☐

Fixation components

	26070 0060 FBRX FRAX BRACKET FBRX	☐
	26070 0060 N FRAX BRACKET N	☐
	26070 0060 PGR FRAX BRACKET PGR	☐

Light altering devices

	26070 0020 N FRAX M KAP N	☐
--	----------------------------------	--------------------------

DELTALIGHT

FRAX MB 92726 DIM5

26010 9265 FBRX

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26070 0050 N FRAX STRAP N

☐

Notes: