
DELTALIGHT



M - DALI PRESENCE AND DAYLIGHT SENSOR (BROADCAST)

REFERENCE 21032 0185



View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
INFORMATION	PRESENCE and DAYLIGHT 0,1W max.

Electrical info	
CLASS	III

For detailed installation instructions, please consult the manual : **21032_0185_HAND.pdf**

WHERE USED

420 20 10 00	SPM20 - PROFILE 1m
420 20 20 00	SPM20 - PROFILE 2m
420 20 30 00	SPM20 - PROFILE 3m
420 52 10 00	SPM52 - PROFILE 1m
420 52 20 00	SPM52 - PROFILE 2m
420 52 30 00	SPM52 - PROFILE 3m
23301 0000	SPM20 - PROFILE
23358 0000	SLM26L - PROFILE
23358 0010	SLM26L - PROFILE 1m
23358 0020	SLM26L - PROFILE 2m
23358 0030	SLM26L - PROFILE 3m
23359 0000	SLM26H - PROFILE
23359 0010	SLM26H - PROFILE 1m
23359 0020	SLM26H - PROFILE 2m
23359 0030	SLM26H - PROFILE 3m
23374 0000	SLM44 - PROFILE
23374 0020	SLM44 - PROFILE 2m
23374 0030	SLM44 - PROFILE 3m
23375 0000	SLM35R - PROFILE
23375 0010	SLM35R - PROFILE 1m
23375 0020	SLM35R - PROFILE 2m
23375 0030	SLM35R - PROFILE 3m
23397 0000	SPM20 ST - PROFILE
23397 0020	SPM20 ST - PROFILE 2m
23397 0030	SPM20 ST - PROFILE 3m
24413 0000	SPM52 - PROFILE

DELTALIGHT

M - DALI PRESENCE AND DAYLIGHT SENSOR (BROADCAST)

21032 0185

Notes: