

LASS-OH!



Lass-Oh! glides through the room as a snake sliding through the greensward, showing off its slim cylindrical contour in combination with the miniature LED clusters hidden inside its body. The variety in shape — straight lines or curved squares and rectangles — in combination with the optional shades make of Lass-Oh! a very decorative lighting solution. Nevertheless, Lass-Oh! can easily be hung in every residential, retail or office project thanks to its low-glare LED dots that are hidden away into the profile.

Specification	
Aperture:	5/16"
Installation Method:	4" J-Box or Power Box
Adjustability:	Fixed
Rating:	IP20 (Damp)

Performance	
LED Maintenance:	L80>60,000h
McAdam Step:	3
CRI:	90
Lass-Oh S606 SP:	4 x 6.1W
Lass-Oh S611 SP:	4 x 6.1W
Lass-Oh S616 SP:	6 x 6.1W
Lass-Oh R65 SP:	3 x 6.1W
Lass-Oh R90 SP:	4 x 6.1W

Specification	2700K	3000K	3500K
Lass-Oh S606 SP:	2102Lm	2159Lm	2248Lm
Lass-Oh S611 SP:	2102Lm	2159Lm	2248Lm
Lass-Oh S616 SP:	3153Lm	3239Lm	3371Lm
Lass-Oh R65 SP:	1577Lm	1619Lm	1686Lm
Lass-Oh R90 SP:	2102Lm	2159Lm	2248Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: LSOS616-SPFL35-B-PCPRB-RMTD1-UNV

Luminaire	Shape	Size	Power*	Optic	CCT	Finish	Style	Installation	Application	Controls***
LSO LASS-OH	S Rounded square/ rectangle	606 620 x 620mm / 24 ^{7/16} " x 24 ^{7/16} "	SP Standard Power	FL 34°	27 2700K 30 3000K 35 3500K	B Black GC Gold Colored	PC Pendant, 4 suspension points for Shape S, 3 for Shape R	PRB Round black coverplate for 4" junction box	RMT Remote Power Supply	D1-UNV 0-10V dim 120-277V D1-347 0-10V dim 347V
		611 620 x 1120mm / 24 ^{7/16} " x 44 ^{3/32} "						PSB Square black coverplate for 4" junction box		
		616 620 x 1620mm / 24 ^{7/16} " x 63 ^{25/32} "						NA No accessory, utilizing 1/2" EMT installation	PBB Power Box Black	D14-UNV 0-10V dim 120-277V / FE ELV dim 120V
	R Round	65 670mm 26"-3/8 90 920mm 36"-7/32								

*** Contact factory for additional dimming options.

Related Products

Lass-Oh L, Dot.Com

DELTALIGHT


www.deltalight.com





Finishing Options

LASS-OH S606 LASS-OH S611 LASS-OH S616 LASS-OH R65 LASS-OH R90




BLACK GOLD COLORED

Accessories



Photometric Data

LASS-OH






Installation Options


REMOTE POWER SUPPLY (With Control D1)

A: 8" x **B:** 2"-3/16" x **C:** 4"-1/4"
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated




PR - COVERPLATE R 104 B




BLACK
Requires 4" junction box

PS - COVERPLATE S 103 B



BLACK
Requires 4" junction box

PBB - POWER BOX



Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D14

- Dimming Control Phase Control or -10V
- Dimming Range 1-100%
- Dim to off yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥90
- THD @ Full Load <20%

Dimmer Compatibility Phase

- Leviton IP1106-1LZ / 6631-2
- Leviton DVELV-303P / MAELV-600

Dimmer Compatibility 0-10V

- Leviton IP710-DLZ
- Leviton DDTV-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.