



# DELTALIGHT



## KIX II PIN 92730

13537 9220 N

AVAILABLE IN  
**ALU GREY** 13537 9220 A  
**ANTHRACITE** 13537 9220 N  
**PINE GREEN** 13537 9220 PGR



 [View on website](#)



### General info

|   |   |
|---|---|
| <b>LOCATION</b>                             | outdoor   |
| <b>INSTALLATION</b>                         | Floor Surface mounted   |
| <b>INGRESS PROTECTION</b>                   | IP65  |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK03  |
| <b>WEIGHT (KG)</b>                          | 1.2   |
| <b>ADJUSTABILITY</b>                        | 180° swiveling, 360° rotatable  |
| <b>INFORMATION</b>                          | REFLECTOR FL-30°<br>INCL.1 x CABLE H05 RN-F 2 x 1mm <sup>2</sup> 2m<br>INCL.LED POWER SUPPLY 350mA-DC |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 100-240V / 50-60Hz |
| <b>CLASS</b>        | II                 |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | E                  |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                 |
| <b>SDCM</b>                        | SDCM1  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L90B10 > 50000                                   |
| <b>BEAMANGLE</b>                   | 30°  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 753lm // 5,8W // 129lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 616lm // 6,7W // 92lm/W                          |

### Options

CBOX  
 IP68 CONNECTION KIT  
 IP68 CONNECTOR 3P

### Accessories

KAP KIX  
 HONEYCOMB KIX

# DELTALIGHT


## KIX II PIN 92730

13537 9220 N

For detailed installation instructions, please consult the manual : [13537\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### Waterproof connection parts



**216 12 00** CBOX

Cutout dimension (mm): 142 x 142




**216 12 01** IP68 CONNECTION KIT




**216 12 02** IP68 CONNECTOR 3P

#### Light altering devices



**232 10 00 N** KAP KIX N



**232 10 03 N** HONEYCOMB KIX N

Notes: