

## SOLI - FORM 90 92767 MDL

27128 9220 B-B



AVAILABLE IN

**BLACK-BLACK** 27128 9220 B-B

**BLACK-FLEMISH GOLD** 27128 9220 B-FG

**WHITE-BLACK** 27128 9220 W-B

**WHITE-WHITE** 27128 9220 W-W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 16,7W / CRI>90 (R9: 50) / 2700K / 2196lm
<b>TM-30 VALUES</b>	Rf: 93 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	67°
<b>LED TECHNICS (LIGHT SOURCE)</b>	2196lm // 16,7W // 131lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1917lm // 19,2W // 100lm/W

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27128\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## SOLI - FORM 90 92767 MDL

27128 9220 B-B

### FINISH YOUR SPECIFICATION


#### SMART 48

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

11

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

11

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

5

Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

13

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

5

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

11

Dimtype: non-dimmable

Cutout dimension (mm): 40

# DELTALIGHT

## SOLI - FORM 90 92767 MDL

27128 9220 B-B

### COMPATIBLE COMPOSABLES

#### SOLISCAPE profile

#### Available Colours



**27111 0020** SOLI - PROFILE 2m



**27111 0030** SOLI - PROFILE 3m



Notes: