





SPY 52 93045 ADM SLIM

19836 9330 W

BESCHIKBAAR IN
ZWART 19836 9330 B
WIT 19836 9330 W



 [Bekijk op website](#)



Algemene info

LOCATIE	binnen
INSTALLATIE	Rail systemen Rail montage
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.4
RICHTBAARHEID	0° tot 90° zwenkbaar, 360° roteerbaar
INFO	REFLECTOR WFL-45° 3F MULTI POWER SLIM ADAPTER 350-700mA Current selection via jumper on adapter Optional REFLECTORS 20° & 30° available

Elektrische info

ELEKTRISCH	220-240V / 50-60Hz
KLASSE	II
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	CB, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 700mA: LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm Or @ 500mA: LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm Or @ 350mA: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 WAARDEN	@ 700mA: rf: 90 / Rg: 99 @ 500mA: rf: 90 / Rg: 99 @ 350mA: rf: 90 / Rg: 99
SMDC	SDCM1
RISK-GROEP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNIEK (LICHTBRON)	@ 700mA: 1467lm // 12,4W // 118lm/W Or @ 500mA: 1089lm // 8,6W // 127lm/W Or @ 350mA: 787lm // 5,8W // 135lm/W
LED TECHNIEK (TOESTEL)	@ 700mA: 939lm // 14,3W // 66lm/W Or @ 500mA: 697lm // 9,9W // 70lm/W Or @ 350mA: 504lm // 6,7W // 75lm/W

DELTALIGHT

SPY 52 93045 ADM SLIM

19836 9330 W

Benodigdheden

SPY 52 TUBE
TRACK 3F DIM


Accessoires

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42


Voor gedetailleerde montage gegevens, consulteer de handleiding : [19836_XXX0_HAND.pdf](#)

VERVOLLEDIG UW SPECIFICATIE


Licht veranderende onderdelen



19810 0010 B HONEYCOMB 42 SINGLE USE B




19810 0020 LINEAR SPREAD LENS 42




19810 0030 SPREAD LENS 42



19810 0040 SOFTENING LENS 42



19810 0050 GLASS SBL 42



19810 0060 B HONEYCOMB 42 DOUBLE USE B

DELTALIGHT

SPY 52 93045 ADM SLIM

19836 9330 W

Maak je product af



19810 0100 B SPY 52 TUBE B

19810 0100 FBR SPY 52 TUBE FBR

19810 0100 FG SPY 52 TUBE FG

19810 0100 GC SPY 52 TUBE GC

19810 0100 W SPY 52 TUBE W

Vervangbare reflector / lens



19810 0180 SPY 52 REFLECTOR 20°



19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°

COMPATIBELE TRACKS

TRACK 3F DIM H

Beschikbare kleuren

200 14 410 TRACK 3F DIM H 1m

1000 m 1.6 kg



200 14 420 TRACK 3F DIM H 2m

2000 m 3.2 kg



200 14 430 TRACK 3F DIM H 3m

3000 m 4.8 kg



TRACK 3F DIM IN

Beschikbare kleuren

200 13 410 TRACK 3F DIM IN 1m






1000 m 1.2 kg



DELTALIGHT

SPY 52 93045 ADM SLIM

19836 9330 W

200 13 420 TRACK 3F DIM IN 2m	2000 m 2.4 kg	
200 13 430 TRACK 3F DIM IN 3m	3000 m 3.5 kg	
TRACK 3F DIM ON		Beschikbare kleuren
200 12 410 TRACK 3F DIM ON 1m	1000 m 1.1 kg	
200 12 420 TRACK 3F DIM ON 2m	2000 m 2.1 kg	
200 12 430 TRACK 3F DIM ON 3m	3000 m 3.1 kg	

Notes: