



SPY 39 PLUG WALLWASH SOFT 930

24178 9000 BROB

AVAILABLE IN

NOIR 24178 9000 B

ALU BROSSÉ 24178 9000 BRA

ANTHRACITE BROSSÉ 24178 9000 BRAT

CUIVRE BROSSÉ 24178 9000 BRCU

OR BROSSÉ 24178 9000 BRG

BRONZE VIEUX BROSSÉ 24178 9000 BROB

FLEMISH BRONZE 24178 9000 FBR

FLEMISH GOLD 24178 9000 FG


ENTIÈREMENT BLANC 24178 9000 FW

COULEUR OR 24178 9000 GC

BLANC 24178 9000 W



0-85°/355°



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Semi-encasté
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° à 85° inclinable, 355° rotatif
INFORMATION	WALLWASH LENS EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	341lm // 6,9W // 49lm/W


Requirements

MOUNTING KIT PLUG O.F.A.
LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : **24178_XXX0_HAND.pdf**

Ceiling Type	Mounting Kit
Plasterboard	24144 0060 - MOUNTING KIT PLUG O.F.A. Required
Concrete + plaster	24144 0060 - MOUNTING KIT PLUG O.F.A. Required
Lintel + plaster	24144 0060 - MOUNTING KIT PLUG O.F.A. Required
Hollow-core slab + plaster	24144 0060 - MOUNTING KIT PLUG O.F.A. Required

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

7


21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

7

les alimentations led

of Fixtures

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC /15W DIM1

Dimtype: 1 à 10 V

Cutout dimension (mm): 30

2

7



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

Dimtype: DALI

Cutout dimension (mm): 45

2

7

SPY 39 PLUG WALLWASH SOFT 930









24178 9000 BROB

	<u>300 48 350 MDL</u> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	2 ☐
Dimtype: non dimmable Cutout dimension (mm): 30		
	<u>300 48 350 WDL</u> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	2 ☐
Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45		
	<u>300 90 61</u> LED POWER SUPPLY MULTI-POWER DIM6	2 ☐
Dimtype: fin de phase ou bouton poussoir Cutout dimension (mm): 56		
	<u>300 90 63</u> LED POWER SUPPLY MULTI-POWER DIM9	4(4) ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82		
	<u>300 90 64</u> LED POWER SUPPLY MULTI-POWER DIM7	3(2) ☐
Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 72		
	<u>300 90 67</u> LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2 ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5	2(2) ☐
Dimtype: DALI Cutout dimension (mm): 72		
	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84		
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7	2(2) ☐
Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55		
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) ☐
Dimtype: DALI Cutout dimension (mm): 55		


DELTALIGHT

SPY 39 PLUG WALLWASH SOFT 930

24178 9000 BROB

	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	4(4)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	3	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

kit de montage

	24144 0060 MOUNTING KIT PLUG O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		

DELTALIGHT

SPY 39 PLUG WALLWASH SOFT 930

24178 9000 BROB

Notes: